

File E206750

Vol 1

Auth. Page 1

Issued: 2000-02-28 Revised: 2012-03-23

FOLLOW-UP SERVICE PROCEDURE (TYPE R)

COMPONENT - MOTOR CONTROLLERS, FLOAT- AND PRESSURE-OPERATED (NKPZ2,NKPZ8)

Manufacturer:

SEE ADDENDUM FOR MANUFACTURER LOCATIONS

123895 (Party Site)

Applicant: (589926-001)

TERMOREGOLATORI CAMPINI - COREL SPA

VIA DON GUANELLA 1

22066 MARIANO COMENSE CO ITALY

123895 (Party Site)

Recognized Company:

SAME AS APPLICANT

(589926-001)

This Follow-Up Service Procedure authorizes the above Manufacturer(s) to use the marking specified by UL LLC, or any authorized licensee of UL LLC, including the UL Contracting Party, only on products when constructed, tested and found to be in compliance with the requirements of this Follow-Up Service Procedure and in accordance with the terms of the applicable service agreement with UL Contracting Party and any applicable Service Terms. The UL Contracting Party for Follow-Up Services is listed on addendum to this Follow-Up Service Procedure ("UL Contracting Party"). UL Contracting Party and UL LLC are referred to jointly herein as "UL."

UL further defines responsibilities, duties and requirements for both Manufacturers and UL representatives in the document titled, "UL Mark Surveillance Requirements" that can be located at the following web-site: http://www.ul.com/fus and in the document titled "UL and Subscriber Responsibilities" that can be located at the following website: http://www.ul.com/responsibilities. Manufacturers without Internet access may obtain the current version of these documents from their local UL customer service representative or UL field representative. For assistance, or to obtain a paper copy of these documents or the applicable Service Terms, please contact UL's Customer Service at http://www.ul.com/global/eng/pages/corporate/contactus, select a location and enter your request, or call the number listed for that location.

The Applicant, the specified Manufacturer(s) and any Recognized Company in this Follow-Up Service Procedure must agree to receive Follow-Up Services from UL Contracting Party. If your applicable agreement is a Global Services Agreement ("GSA") with an effective date of January 1, 2012 or later and this Follow-Up Service Procedure is issued on or after that effective date, the Applicant, the specified Manufacturer(s) and any Recognized Company will be bound to a Service Agreement for Follow-Up Services upon the earliest by any Subscriber of use of the prescribed UL Mark, acceptance of the factory inspection, or payment of the Follow-Up Service fees which will incorporate such GSA, this Follow-Up Service Procedure and the Follow-Up Service Terms which can be accessed by clicking here:
http://www.ul.com/contracts/Terms-After-12-31-2011. In all other events, Follow-Up Services will be governed by and incorporate the terms of your applicable service agreement and this Follow-Up Service Procedure.

File E206750 Vol 1 Auth. Page 2 Issued: 2000-02-28 Revised: 2012-03-23

It is the responsibility of the Recognized Company to make sure that only the products meeting the aforementioned requirements bear the authorized Marks of UL LLC, or any authorized licensee of UL LLC.

This Follow-Up Service Procedure contains information for the use of the above Manufacturer(s) and representatives of UL and is not to be used for any other purpose. It is provided to the Manufacturer with the understanding that it will be returned upon request and is not to be copied in whole or in part.

This Follow-Up Service Procedure, and any subsequent revisions, is the property of UL and is not transferable. This Follow-Up Service Procedure contains confidential information for use only by the above named Manufacturer(s) and representatives of UL and is not to be used for any other purpose. It is provided to the Subscribers with the understanding that it is not to be copied, either wholly or in part unless specifically allowed, and that it will be returned to UL, upon request.

Capitalized terms used but not defined herein have the meanings set forth in the GSA and the applicable Service Terms or any other applicable UL service agreement.

UL shall not incur any obligation or liability for any loss, expense or damages, including incidental, consequential or punitive damages arising out of or in connection with the use or reliance upon this Follow-Up Service Procedure to anyone other than the above Manufacturer(s) as provided in the agreement between UL LLC or an authorized licensee of UL LLC, including UL Contracting Party, and the Manufacturer(s).

UL LLC has signed below solely in its capacity as the accredited entity to indicate that this Follow-Up Service Procedure is in compliance with the accreditation requirements.

William R. Carney Director North American Certification Program File E206750 Vol 1 Addendum To Page 1 Issued: 2000-02-28 Authorization Page Revised: 2012-03-23

LOCATION

123895 (Party Site)

(589926-001) TERMOREGOLATORI CAMPINI - COREL SPA

VIA DON GUANELLA 1

22066 MARIANO COMENSE CO ITALY

Factory ID:

UL Contracting Party for above site is: UL AG

File E206750 Project 07CA45870

2008-01-25

REPORT

on

COMPONENT - FLOAT-AND-PRESSURE OPERATED SWITCHES - COMPONENT

TERMOREGOLATORI CAMPINI - COREL SPA MARIANO COMENSE (CO), ITALY

Copyright © 2008 Underwriters Laboratories Inc. $\ensuremath{\mathbb{R}}$

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce the latest pages of that portion of this Report consisting of this Cover Page through Page 1.

File E206750 Vol. 1 Sec. 3 Page 1 Issued: 2008-01-25 and Report

DESCRIPTION

PRODUCT COVERED:

USR, CNR - Component - Float and Pressure Operated Switches, Model TY60V.

GENERAL:

This device is an open type pressure switch provided with Normally Open (NO) contact, intended for industrial and or household use.

The device has not been investigated for performing limiting or safety functions.

ELECTRICAL RATINGS:

Type model: TY60V

Output Contact: 250 V ac, 5 A resistive - 100,000 Cycles

Operating Pressure: 5 bars ± 8%

Surrounding Air temperature: 125°C

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE'S USE):

USR indicates evaluation to UL 508, Standard for "Industrial Control Equipment", Seventeenth Edition, Dated January 28, 1999.

CNR indicates investigation to Canadian Standard C22.2 No. 14-M95, Standard for "Industrial Control Equipment" dated April 2005.

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc. $\,$

Conditions of Acceptability - When installed in the final use equipment, etc., the following are among the considerations to be made:

- The device shall be installed in compliance with the enclosure, mounting, spacing, and segregation requirements of the ultimate application.
- 2. The rating recorded herein shall be judged in the ultimate application.
- 3. The quick-connect style terminals were not evaluated for field wiring connections. The suitability of connections to these terminals, including temperature and pullout, shall be determined in the ultimate application.
- 4. The spacing has been verified in according to the Table 36.1, column B.