



File E82842

Vol 2

Auth. Page 1

Issued: 1998-10-07

Revised: 2013-02-08

FOLLOW-UP SERVICE PROCEDURE
(TYPE R)

COMPONENT - TEMPERATURE-INDICATING AND -REGULATING EQUIPMENT
(XAPX2,XAPX8)

Manufacturer: SEE ADDENDUM FOR MANUFACTURER LOCATIONS

123895 (Party Site)
Applicant: TERMOREGOLATORI CAMPINI - COREL SPA
(589926-001) VIA DON GUANELLA 1
22066 MARIANO COMENSE CO ITALY

123895 (Party Site)
Recognized Company: SAME AS APPLICANT
(589926-001)

This Follow-Up Service Procedure authorizes the above Manufacturer(s) to use the marking specified by UL LLC, or any authorized licensee of UL LLC, including the UL Contracting Party, only on products when constructed, tested and found to be in compliance with the requirements of this Follow-Up Service Procedure and in accordance with the terms of the applicable service agreement with UL Contracting Party and any applicable Service Terms. The UL Contracting Party for Follow-Up Services is listed on addendum to this Follow-Up Service Procedure ("UL Contracting Party"). UL Contracting Party and UL LLC are referred to jointly herein as "UL."

UL further defines responsibilities, duties and requirements for both Manufacturers and UL representatives in the document titled, "UL Mark Surveillance Requirements" that can be located at the following web-site: <http://www.ul.com/fus> and in the document titled "UL and Subscriber Responsibilities" that can be located at the following website: <http://www.ul.com/responsibilities>. Manufacturers without Internet access may obtain the current version of these documents from their local UL customer service representative or UL field representative. For assistance, or to obtain a paper copy of these documents or the applicable Service Terms, please contact UL's Customer Service at <http://www.ul.com/global/eng/pages/corporate/contactus>, select a location and enter your request, or call the number listed for that location.

The Applicant, the specified Manufacturer(s) and any Recognized Company in this Follow-Up Service Procedure must agree to receive Follow-Up Services from UL Contracting Party. If your applicable agreement is a Global Services Agreement ("GSA") with an effective date of January 1, 2012 or later and this Follow-Up Service Procedure is issued on or after that effective date, the Applicant, the specified Manufacturer(s) and any Recognized Company will be bound to a Service Agreement for Follow-Up Services upon the earliest by any Subscriber of use of the prescribed UL Mark, acceptance of the factory inspection, or payment of the Follow-Up Service fees which will incorporate such GSA, this Follow-Up Service Procedure and the Follow-Up Service Terms which can be accessed by clicking here: <http://www.ul.com/contracts/Terms-After-12-31-2011>. In all other events, Follow-Up Services will be governed by and incorporate the terms of your applicable service agreement and this Follow-Up Service Procedure.

It is the responsibility of the Recognized Company to make sure that only the products meeting the aforementioned requirements bear the authorized Marks of UL LLC, or any authorized licensee of UL LLC.

This Follow-Up Service Procedure contains information for the use of the above Manufacturer(s) and representatives of UL and is not to be used for any other purpose. It is provided to the Manufacturer with the understanding that it will be returned upon request and is not to be copied in whole or in part.

This Follow-Up Service Procedure, and any subsequent revisions, is the property of UL and is not transferable. This Follow-Up Service Procedure contains confidential information for use only by the above named Manufacturer(s) and representatives of UL and is not to be used for any other purpose. It is provided to the Subscribers with the understanding that it is not to be copied, either wholly or in part unless specifically allowed, and that it will be returned to UL, upon request.

Capitalized terms used but not defined herein have the meanings set forth in the GSA and the applicable Service Terms or any other applicable UL service agreement.

UL shall not incur any obligation or liability for any loss, expense or damages, including incidental, consequential or punitive damages arising out of or in connection with the use or reliance upon this Follow-Up Service Procedure to anyone other than the above Manufacturer(s) as provided in the agreement between UL LLC or an authorized licensee of UL LLC, including UL Contracting Party, and the Manufacturer(s).

UL LLC has signed below solely in its capacity as the accredited entity to indicate that this Follow-Up Service Procedure is in compliance with the accreditation requirements.

William R. Carney
Director
North American Certification Program

File E82842 Vol 2 Addendum To Page 1
Authorization Page

Issued: 1998-10-07
Revised: 2013-02-08

LOCATION

(100098-388) 939123 (Party Site)
TERMOREGOLATORI CAMPINI COREL SRL
DUMBRAVITA
STR GRAMMA NR 10A JUD
TIMIS ROMANIA
Factory ID: None
UL Contracting Party for above site is: UL AG

I N D E X

Type	Section	Report Date	Approval
TY95	1	1998-07-04	B
TY95-H, TY95-Z TY95-HS	2	2003-11-14	B
TY95-S, TY95-S1	3	2003-11-17	B
Regulating Thermostat Type TY62-A	4	2008-04-08	B
Limiting Thermostat Type TY62-R	5	2008-04-15	B

Approval Abbreviation:

A - Evaluated to United States Standards Only - Recognized

B - Evaluated to United States and Canadian National Standards - Recognized

C - Evaluated to Canadian National Standards Only - Recognized

File E82842
Project 07CA43098

April 15, 2008

REPORT

on

COMPONENT - TEMPERATURE INDICATING AND REGULATING EQUIPMENT

TERMOREGOLATORI CAMPINI S.P.A.
MARIANO COMENSE, COMO, ITALY

Copyright © 2008 Underwriters Laboratories Inc.®

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 3.

DESCRIPTION

PRODUCT COVERED:

USR, CNR - Component - Manual Reset Temperature Limiting Thermostat (thermal cut-out) type TY62-R.

GENERAL CHARACTER:

This device is a manual reset, bimetal actuated, DPST, thermal cut-out thermostat with normally closed (NC) contacts.

Function Description

The device is provided with a bimetal disc that directly switches the contact by means of the transfer pin, changing the position of the moveable contact support. The moveable contact support works in combination with the reset button in order to reset the contacts and to prevent the thermostat from resetting automatically when the bimetal cools below its switch temperature. A manual action is required to reset the movable contact support.

The opening set-point temperature may be selected from 75°C to 180°C with manufacturing deviation of ± 4 K, and ± 8 K of Drift.

This device has been subjected to a 6000 cycles endurance test (1000 cycles with current and 5000 cycles with out current).

The Manual Reset Temperature Limiting Thermostat (thermal cut-out) has been declared by the manufacturer, and it has been evaluated for type 2.BH action. It means that thermostat is intended for limiting application (thermal cut-out), able to provide micro-disconnection and designed in order that the contacts cannot be prevented from opening and which may automatically reset to the closed position if the reset means is held in the reset position. In addition the thermostat doesn't reset automatically at -35°C with the reset mechanism in the normal position.

RATINGS: for more details about ratings see ILL. 1.

Electrical - 250 Vac, 16 resistive; 3 A Inductive non-motor (general purpose) Load, 6K cycles

Temperature - Maximum ambient temperature 180°C

Deviation ± 4 K /Drift ± 8 K

The trip temperature may be selected progressively each 5K and only multiples of 5K.