

INDEPENDENT

# BATTERY CERTIFICATE



CERTIFICATE NUMBER: 6AF73A12-C8BC-497A-9823-5D2CF46AB9F1

VEHICLE

BRAND: Tesla  
MODEL: Model 3 - 82,1 kWh

MILEAGE: 40,672 km  
VIN: 5YJ3E7ECXMF963697

EXECUTED BY: Carla AB

DATE AND TIME:  
18/02/2026, 07:46:46

RESULTS

## STATE OF HEALTH (SOH)

93.9 %

ENERGY 73kWh | 78kWh




WLTP RANGE 576km | 614km

RATING

## BENCHMARKING

How does your vehicle compare to comparable vehicles?



CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓



EVALUATION


## EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

*Marcus Berger*

Dr. Marcus Berger, CEO



### ENERGY

	Gross	Net (Nominal)	Usable
Current:	77.1kWh	73.1kWh	68.7kWh
New:	82.1kWh	77.9kWh	73.2kWh

### RANGE

	WLTP	Typical
Current:	513-576km	411km
New:	547-614km	438km

### EXECUTION PROTOCOL

<b>AVILOO Box connected.</b>	<b>08:46:42</b>
FLASH Test started.	✓
Vehicle detected.	✓
Starting data acquisition.	✓
Finished data acquisition.	✓
Analyzing data.	✓
Analysis completed.	✓

### SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

### BMS


	Value	Status
BMS State of Charge (SoC)*:	39%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	87%	
SoH calculation accuracy:		✓

### MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	13.0°C	13.5°C	0.5°C	✓
Cell Voltage	3.722V	3.730V	8mV	✓
Pack Voltage	357.6V			
Average Current	-2.0A			

### CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	3.729	3.729	3.729	3.729	3.729	3.729	3.730	3.729	3.729	3.728	3.729	3.729	3.729	3.729	3.729	3.728	3.729	3.729	3.729	3.729
21 - 40	3.729	3.729	3.729	3.729	3.729	3.729	3.729	3.728	3.729	3.729	3.729	3.729	3.729	3.729	3.728	3.729	3.729	3.728	3.729	3.729
41 - 60	3.729	3.728	3.728	3.728	3.728	3.728	3.728	3.728	3.729	3.729	3.728	3.729	3.729	3.729	3.722	3.729	3.729	3.728	3.729	3.729
61 - 80	3.729	3.730	3.729	3.729	3.729	3.729	3.729	3.730	3.729	3.729	3.728	3.729	3.729	3.729	3.728	3.728	3.728	3.728	3.728	3.728
81 - 96	3.728	3.728	3.728	3.728	3.728	3.728	3.728	3.728	3.728	3.727	3.728	3.728	3.728	3.728	3.728	3.727	/	/	/	/



\*The values shown here were not calculated by AVILOO but correspond to the values read out from the battery management system (BMS) and were calculated by the manufacturer. AVILOO therefore assumes no liability for their accuracy.

**DISCLAIMER:** The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.