



FLASH TEST REPORT

Execution

State of charge **70 %**
Date 09/06/2025 14:56:06
Executed by Carla AB

Vehicle

Brand Polestar
Model 2 - 82 kWh
VIN YSMVSFDE5RL238189
Mileage 23,819 km

Analysis Result

AVILOO SCORE

100
/ 100

High voltage battery usage and history
Analysis of charging & driving behavior

70 / 70

High voltage battery performance
Analysis of cell voltages and module temperatures.

30 / 30

High voltage battery control unit
Check of signals and calculations of the battery management control unit.



Vehicle communication interface
Check of communication via the diagnostic interface.



Dr. Marcus Berger
CEO and Partner

DI Wolfgang Berger MBA
CSO and Founder

DI Nikolaus Mayerhofer
CTO and Founder



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

- 14:56:02
- AVILOO Box connected.
- ✓
- FLASH Test started.
- ✓
- Starting data acquisition.
- ✓
- Vehicle detected.
- ✓
- Finished data acquisition.
- ✓
- Analyzing data.
- ✓
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

| | |
|---------|---------------------|
| Date | 09/06/2025 14:56:06 |
| Mileage | 23,819 km |
| VIN | YSMVSFDE5RL238189 |

Measurements High Voltage System

| | |
|---|----------|
| Battery temperature | 17.19 °C |
| Maximum cell temperature deviation | 1.23 °C |
| Pack voltage | 435.7 V |
| Maximum cell voltage deviation | 11 mV |
| Peak current during check | -2.5 A |
| State of Health (SoH - read from car manufacturer)* | 101.29 % |

fastcheck.certificate.explanationFooterText

