

INDEPENDENT BATTERY CERTIFICATE



CERTIFICATE NUMBER: F56AA832-61EB-4AF6-87D0-425AF1C64AF5

VEHICLE

BRAND: MG Automotive

MILEAGE: 27,519 km

EXECUTED BY: Carla AB

MODEL: ZS EV - 72,6 kWh

VIN: LSJW74090NZ055710

DATE AND TIME:

29.01.2026, 17:20:55

RESULTS

STATE OF HEALTH (SOH)

95.1 %

ENERGY

65kWh | 68kWh


WLTP RANGE

419km | 440km

RATING

BENCHMARKING

How does your vehicle compare to comparable vehicles?



CHECKS

Battery Management System (BMS)



Battery Sensor



Battery Measurements



Battery Cell Voltages



Vehicle Communication




EVALUATION

GOOD HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in good condition.

The drive battery is therefore officially AVILOO Certified.

Dr. Marcus Berger, CEO



ENERGY

Gross	Net (Nominal)	Usable
Current: 69.1kWh	65.0kWh	62.1kWh
New: 72.6kWh	68.3kWh	65.3kWh

RANGE

	WLTP	Typical
Current:	419km	306km
New:	440km	322km

EXECUTION PROTOCOL

AVILOO Box connected. 17:20:52

- FLASH Test started. ✓
- Vehicle detected. ✓
- Starting data acquisition. ✓
- Finished data acquisition. ✓
- Analyzing data. ✓
- Analysis completed. ✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS

	Value	Status
BMS State of Charge (SoC)*:	84%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	94%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	-4.5°C	-4.0°C	0.5°C	✓
Cell Voltage	4.079V	4.099V	20mV	✓
Pack Voltage	392.1V			
Average Current	-1.8A			

*The values shown here were not calculated by AVILOO but correspond to the values read out from the battery management system (BMS) and were calculated by the manufacturer. AVILOO therefore assumes no liability for their accuracy.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOOs algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.