SCAME

205.A52-DD

PILLAR BE-A

Type 2 3P+N+E 32A 400V~ 22kW 63A 400V
3P+N+E IP54 IK10

Product Approvals

TECHDATA

Commercial series	BE-A Series
Type of product	PILLAR BE-A
Synthetical description	PILLAR BE-A
Material	VARNISHED METAL
EV standard	Type 2 3P+N+E 32A 400V~ 22kW
Rated current	63A
Rated voltage	400V
Working frequency	50/60Hz
Poles	3P+N+E
Protection degree IP	IP54
Working temperature	-30°C/+50°C
Protection degree IK	IK10
Colour	BRONZE
Mounting version	ON TURRET
Dimensions	220x1466x300mm

STANDARDS AND LAWS

IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive