



205.W17-U0

WALL BOX CABLE+SOCKET T2

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V
3P+N+E IP54 IK08 Type 2 4m

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|------------------------------|-----------------------------------|--|
| Commercial series | BE-W Series | IEC 61439-7 (2018) | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Type of product | WALL BOX CABLE+SOCKET T2 | | |
| Synthetical description | WALL BOX CABLE+SOCKET T2 | EN IEC 61851-1 (2019) | [European Standard] Electric vehicle conductive charging system - Part 1: General requirements |
| Material | ENGINEERING PLASTIC | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| EV standard | Type 2 3P+N+E 32A 400V~ 22kW | DIRECTIVE EMC 2014/30/UE | [European Directives] Electromagnetic Compatibility Directive |
| With integrated cable | Type 2 | | |
| Cable length | 4m | | |
| Cable section | 5G6+1x0,5mm ² | | |
| Rated current | 32A | | |
| Rated voltage | 400V | | |
| Working frequency | 50/60Hz | | |
| Poles | 3P+N+E | | |
| Protection degree IP | IP54 | | |
| Working temperature | -30°C/+50°C | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK08 | | |
| Colour | ANTHRACITE | | |

| | |
|------------------|------------------|
| Mounting version | SURFACE MOUNTING |
| Dimensions | 235x370x115mm |