

Product Data Sheet

GWJ2103W

JOINON range



The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

INPUT	-	Socket/Connector Nr. (Type)	2 (Type 2 vandal-proof socket, with shutters)
Terminal blocks	2 x (5 x 10 mm²)	Charging activation	Remotely managed, via OCPP 1.6J
Curent nominal	64 A	Human Interface	LED RGB and TFT Display
Total power	44 Kilowatt	Connectivity	LAN,WIFI,4G
OUTPUT	-	MECHANICAL FACTS	-
Tensiune nominală	400 V	Mounting and installation	Wall mount
Curent alimentat (max)	32 A per socket	Culoare	Grey, Headboard RAL 7011
Putere max.	22 kW per socket	Material	Steel sheet
Thermal-magnetic protection	Currently not present	External treatments	Anti-corrosion and anti-graffiti
Tip de protecție diferențială	Currently not present	Clasă de protecție IP	IP55
Contor energie	YES (MID)	Cod IK	IK10
DC Leakage check	Currently not present	Temperatură de operare	-25 +50 °C
(Auto)restart electrical protections	Currently not present	Customizations	Yes (front)



DIMENSIONAL





TECHNICAL SYMBOLOGY

IP IK

IP55 IK10

STANDARDS/APPROVALS

UK C€

GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 03/02/2023 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice