



G-2B-R

Detect gasoline leaks early to prevent personal injury and possible explosions.

ON BOARD, ON GUARD!

PACKAGE CONTENTS:

Gasoline Detector G2BS-N01-D

(2) Plastic Fuel Sensors FS-T01-S

(2) Extension Cables, **FS-X01 CABLE 20'** 20 ft. (6 m)

Manual 18140

INSTALLATION:

- 1 Drill a 2-1/8 in. (54 mm) round hole
- 2 Install assembly through the hole and secure with threaded mounting nut
- 3 Mount sensors
- 4 Plug in cables
- 5 Connect power and ground wires to a 9-30 VDC source

FEATURES / SPECIFICATIONS:

- Xintex Detector with(2) Gasoline Sensors
- 2-5/8 in. (67 mm) Square Display with LEDs & Silence/Test Button
- ▶ 68 dBA Alarm will Sound and Red LED will light at 20% of the LEL
- ▶ Simple Installation
- ▶ 9-30 VDC

- ➤ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- Reverse Polarity Protected
- Current Draw @ 12 VDC:
- Nominal: 95 mA
- Maximum: 150 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection** and **control systems**.

Pre-engineered and custom engineered systems are available.



XINTEX

**STATE STATES STATES