



P-1B-R

Detect propane leaks early to prevent personal injury and possible explosions.

ON BOARD, ON GUARD!

PACKAGE CONTENTS:

Xintex Propane (LPG) P1BR-N01-D

Detector

Plastic Fuel Sensor FS-T01-S

Extension Cable,

20 ft. (6 m)

FS-X01 CABLE 20'

Manual 18142

INSTALLATION:

- 1 Drill α 2-1/16 in. (52 mm) round hole
- 2 Install helm assembly through the hole and secure with threaded mounting nut
- 3 Mount sensor
- 4 Plug in cable
- 5 Connect power and ground wires to a 9-30 VDC source

FEATURES / SPECIFICATIONS:

- Xintex Detector with Sensor for Propane (LPG)
- 2-3/16 in. (56 mm) Round Black Display with LEDs
 & Silence/Test Button
- 68 dBA Alarm will Sound
 & Red LED will Light at
 20% of the LEL
- ▶ Simple Installation

- ▶ 9-30 VDC
- Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- Reverse PolarityProtected
- ▶ Current Draw @ 12 VDC:
 - Nominal: 55 mA
 - Maximum: 95 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection and control systems**.

Pre-engineered and custom engineered systems are available.



