



PROPANE FUME DETECTOR WITH TWO SENSORS

P-2BNV-R



Detect propane leaks early and automatically shut off gas supply to prevent personal injury and possible explosions.

ON BOARD, ON GUARD!

PACKAGE CONTENTS:

Xintex Propane (LPG) Detector	P2BS-S01-D
(2) Plastic Fuel Sensors	FS-T01-S
(2) Extension Cables, 20 ft. (6 m)	FS-X01 CABLE 20'
Manual	18143

INSTALLATION:

- 1 Drill a 2-1/8 in. (54 mm) round hole
- 2 Install helm assembly through the hole and secure with threaded mounting nut
- 3 Mount sensors
- 4 Plug in cables
- 5 Wire to **existing** solenoid valve
- 6 Connect power and ground wires to a 9-30 VDC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with (2) Sensors for Propane (LPG)
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ 2-5/8 in. (67 mm) Square Black Display with LEDs & Silence/Test Button
- ▶ Reverse Polarity Protected
- ▶ 68 dBA Alarm will Sound & Red LED will light at 20% of the LEL
- ▶ Current Draw@ 12 VDC: - Nominal: 95 mA - Maximum: 150 mA
- ▶ Simple Installation
- ▶ For Use with Existing Solenoid Valve & Adapter
- ▶ 9-30 VDC

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection and control systems**.

Pre-engineered and custom engineered systems are available.



MADE IN THE USA



XINTEX



(616) 735-9380 fireboy-xintex.com

O-379 Lake Michigan Dr NW / Grand Rapids, MI 49534