User-friendly operation

Easy to handle; easy to see how it works at first glance
Controllable discharge
Evident safety pin to prevent extinguisher from being unintentionally triggered
Frost-resitant up to -30°C (only SF 2 JM 5)
Suitable for electrical systems of up to 1,000 volts at a safety distance of 1 m

▶ Intelligent Design

Compact and stable valve assembly
Broad spectrum of use for fire
classes A and B
Extinguishing power due to
cooling and smothering

Also available with high performance power Rechargeable

With weather-resistant wall bracket

▶ Best Quality

High-grade steel cylinder with high-quality outer coating and resistant internal layer adding extra protection Push-button valve made of impact-resistant plastic; squeeze grip valve made from brass

Weather and UV-resistant individual parts

▶ Optimale Service

- Service-friendly: Easy refilling
- Low-maintenance: Easy (dis-) assembly
- Cost-effective: Standardized spare parts, special tools are not required

▶ Approvals

According to EN 3 (national approvals for different countries) According to MED 96/98/EG Tested Safety GS

Mini Foam - Stored Pressure



DIN EN 3









▶ Extinguishing Effect



These handy foam extinguishers are the ideal solution for incipient fires of classes A and B. Due to their low specific density foam forms a film of water and is able to create a closed, vapour-tight, watery-film on the surface of the burning material even if this is a liquid. This locking layer prevents vapour and gasses escaping and cuts the supply of oxygen to the burning material. The fire is effectively suffocated. Foam also has a cooling effect due to its high water content.

The foam can be easily removed later. Due to greatly reduced fluorine content, these Jockel bio foams are much more environmentally friendly. Jockel does not use foam concentrate with perfluorooctane sulfonate (PFOS) or perfluorooctanoic acid (PFOA). The high-performance bio extinguisher Plus and Super have an even more effective extinguishing effect thanks to the optimal composition of the extinguishing medium, a greater quantity of extinguishing substances and careful calibration.

▶ For the love of the environment

- Biological extinguishing foams with powerful green formulation with greatly reduced fluorine content and improved biodegradability
- Future-proof formulations based on C6 fluorotelomers;
 Substitutions of PFT by polyFT
- Without PFOA and PFOS
- · Reduced packaging material
- From energy-conscious production



▶ Technical Data

(Distribution Name) SF 2 JM 5	with DH 25-011-35	Agent 2 Foam-		55	Range -20°C to +60°C	Air/N ₂	Time/Range 11 sec.	approx.	approx.	approx.
Type	Code	Capacity/	_ Rat	ing	Temperature	Propellant	Discharge	Height	Width	Weight