

► **User-friendly operation**

Easy to handle; easy to see how it works at first glance
 Controllable discharge
 Evident safety pin to prevent extinguisher from being unintentionally triggered
 Agent is freeze protected up to -30°C and und not electrical conducting
 Suitable for electrical systems of up to 1,000 volts at a safety distance of 1 m.

► **Intelligent Design**

Compact and stable valve assembly
 Broad spectrum of use for fire classes A, B, and C
 Extinguishing power due to anticatalytic effect
 Also available with high performance power
 Rechargeable
 With weather-resistant wall or vehicle bracket

► **Best Quality**

High-grade steel cylinder with high-quality outer coating adding extra protection
 Push-button valve made of impact-resistant plastic; squeeze grip valve made from brass
 Weather and UV-resistant individual parts

► **Optimale Service**

Cost-effective due to standardized spare parts; special tools are not required

handy & compact

Mini Powder - Stored Pressure

DIN EN 3



► **Extinguishing Effect**



These powder extinguishers can be used for all incipient fires of classes A, B and C. The extinguishing effect of the Jockel standard powder for fire classes A, B and C is based on an anticatalytic effect. This means that the intervention of the powder particles in the combustion process causes a chain termination reaction. For fire class A (smouldering fires), the extinguishing powder also has a barrier effect on the burning material - it forms molten layers (smothering sinter layers). In this way, the diffusion of oxygen into the source of the fire is prevented as is the heating of the immediate surroundings of the fire, nor can the fire reignite.

The high-performance extinguishers Plus, Super and Superplus have a more effective extinguishing effect thanks to the optimal composition of the extinguishing medium, a greater quantity of extinguishing substances and the careful calibration of the extinguishing medium with the extinguishing device.

► **For the love of the environment**

- Harmless for humans and animals*
- ABC extinguishing powder according to EN 615 with environmentally friendly components
- Reduced packaging material
- From energy-conscious production



*if used correctly in case of fire

► **Technical Data**

Type (Distribution Name)	Code	Capacity/ Agent	Rating			Temperature Range	Propellant	Discharge Time/Range	Height approx.	Width approx.	Weight approx.
			A	B	C						
PS 1 J 8 PS 1 JM 8	FH 14-500-35 FH 14-501-35	1 kg ABC Standard	8	34	a	-30°C to +60°C	Air/N ₂	7 sec. 7 m	268 mm	120 mm	2,1 kg
PS 2 J 13 PS 2 JM 13	FH 24-500-35 FH 24-501-35	2 kg ABC Standard	13	89	a	-30°C to +60°C	Air/N ₂	10 sec. 9 m	358 mm	130 mm	3,6 kg
PL 1 J 8 PL 1 JM 8	DH 14-580-35 FH 14-587-35 DH 14-581-35 FH 14-588-35	1 kg ABC Standard	8	34	a	-30°C to +60°C	Air/N ₂	8 sec. 7 m	300 mm	135 mm	2,0 kg
PL 2 J 13 PL 2 JM 13	DH 24-580-35 FH 24-587-35 DH 24-581-35 FH 24-588-35	2 kg ABC Standard	13	89	a	-30°C to +60°C	Air/N ₂	11 sec. 9 m	380 mm	145 mm	3,5 kg

M: Pressure Gauge / Manometer DH: Wall Bracket FH: Vehicle Bracket
 *MED-Approval for all 2 kg models.

Products can differ from actual products. Subject to modifications without notice and errors. 12/15