

Standard series

special fire extinguishers for grease fire

Extinguishing agent ABF



If you ever stood in front of a burning pan or a fryer you know how fast fat can ignite itself. If then the wrong extinguishing agent is used such as water, it will violently vaporize and will spray burning fat everywhere.

For a successful fire fighting of grease fire (fire class F) Jockel provides you with special extinguishers which also can be used in different fields and are suitable for fire classes A, B, and F.



Special conditions require particular solutions. Jockel grease fire extinguishers contain a highly concentrated saline solution which causes saponification when sprayed on burning oil. In this way the fire is smothered.



MADE IN GERMANY



Safe handling

An extinguisher with 6 kg extinguishing agent naturally has a significant weight. The larger the device, the more urgent the need for a comfortable carry handle. Plus: we considered the weight of each individual part, so the fire extinguisher would be as light as possible.

Areas of application

- ▶ Restaurants & take-aways
- ▶ Canteen kitchens
- ▶ Bakeries

Technical data

Type (Brand name)	Code	Capacity/agent	Rating			Temperature range	Propel-lant	Discharge time/range	Height approx.	Width approx.	Weight approx
			A	B	C						
F 3 LJM 8	32-301-35	3 l aqueous solution for grease fires	8	55	75	-30°C to +60°C	Air/N ₂	17 sec. 7 m	375 mm	230 mm	6,3 kg
F 6 LJM 13 incl. lance	60-319-35	6 l aqueous solution for grease fires	13	113	75	+5°C to +60°C	Air/N ₂	39 sec. 4 m	592 mm	240 mm	11,3 kg

Product images may slightly deviate. Subject to technical changes. Version from 10/17