

Zyxel GS1915-8EP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz

Marke : Zyxel

Artikel-Code: GS1915-8EP-EU0101F

Produktname : GS1915-8EP

Zyxel GS1915-8EP. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. Vollduplex. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 16 Gbit/s. Netzstandard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE.... Netzstecker: AC-Eingangsbuchse. Power over Ethernet (PoE)



Management-Funktionen		Design	
Switch-Typ *	Managed	LED-Anzeigen	✓
Switch-Ebene	L2	Elektromagnetische Verträglichkeit	LVD EN60950-1, BSMI CNS14336-1
Quality of Service (QoS) Support	✓	Leistungen	
Web-basiertes Management	✓	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1641000 h
Systemereignisprotokoll	✓	Energie	
MIB Unterstützung	RFC 1213 MIB II, RFC 2819, RFC 1215, RFC 1493	Energiequelle *	AC
Anschlüsse und Schnittstellen		AC Eingangsspannung	200 - 240 V
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8	AC Eingangsfrequenz	50 - 60 Hz
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Stromverbrauch (max.)	72 W
Anzahl Gigabit Ethernet (Kupfer) Anschlüsse	8	Power over Ethernet (PoE)	
Netzstecker	AC-Eingangsbuchse	Power over Ethernet (PoE) *	✓
Netzwerk		Anzahl Power over Ethernet (PoE) Anschlüsse	8
Netzstandard *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Gesamtleistung Power over Ethernet (PoE)	60 W
10G-Unterstützung *	✗	Betriebsbedingungen	
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Betriebstemperatur	0 - 40 °C
Vollduplex	✓	Temperaturbereich bei Lagerung	-40 - 70 °C
Unterstützung Datenflusssteuerung	✓	Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Broadcast-Sturmkontrolle	✓	Luftfeuchtigkeit bei Lagerung	10 - 95%
Ratenbeschränkung	✓	Wärmeableitung	245,52 BTU/h
Auto MDI/MDI-X	✓	Gewicht und Abmessungen	
VLAN-Unterstützung	✓	Breite	250 mm
Anzahl der VLANs	8	Tiefe	104 mm
Datenübertragung		Höhe	27 mm
Routing-/Switching-Kapazität *	16 Gbit/s	Gewicht	620 g
Transferrate	11,9 Mpps	Lieferumfang	
MAC-Adressentabelle *	8000 Eintragungen	Mitgelieferte Kabel	AC
Jumbo Frames Unterstützung	✓	Schnellstartübersicht	✓
		Benutzerhandbuch	✓
		Betriebsanleitung	✓

Datenübertragung		Verpackungsdaten	
Jumbo-Frames	9000	Verpackungsbreite	302 mm
Datenpaket-Pufferspeicher	0,525 MB	Verpackungstiefe	227 mm
Sicherheit		Verpackungshöhe	64 mm
IGMP-Snooping	✓	Paketgewicht	1,4 kg
MAC Adressen Filtern	✓	Zertifikate	
SSH-/SSL-Unterstützung	✓	Zertifizierung	CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438
Multicast-Funktionen		Logistikdaten	
Multicast Unterstützung	✓	Warentarifnummer (HS)	85176990
Protokolle			
Management-Protokolle	SNMP v1,v2,v3, RMON (1,2,3,9)		
Design			
Produktfarbe	Schwarz		



4718937621934

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.