

ZYXEL

## Zyxel GS1100-10HP v2 Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz

Marke : Zyxel

Artikel-Code: GS1100-10HP-EU0102F

Produktname : GS1100-10HP v2



Zyxel GS1100-10HP v2. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 20 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE.... DC input Spannung: 54 V. Netzstecker: DC-Anschluss. Power over Ethernet (PoE). Wandmontage



| Management-Funktionen                              |  | Power over Ethernet (PoE)                   |             |
|--|--|---|-------------|
| Switch-Typ *                                       | Unmanaged  | Power over Ethernet (PoE) *                 | ✓           |
| Anschlüsse und Schnittstellen                      |  | Anzahl Power over Ethernet (PoE) Anschlüsse | 8           |
| Anzahl der basisschaltenden RJ-45 Ethernet Ports * | 8  | Gesamtleistung Power over Ethernet (PoE)    | 130 W       |
| Basic Switching RJ-45 Ethernet Ports-Typ *         | Gigabit Ethernet (10/100/1000)   | Betriebsbedingungen                         |             |
| Menge SFP-Modul-Steckplätze                        | 2  | Betriebstemperatur                          | 0 - 50 °C   |
| Netzstecker  | DC-Anschluss   | Temperaturbereich bei Lagerung              | -40 - 70 °C |
| Netzwerk   |  | Relative Luftfeuchtigkeit in Betrieb        | 10 - 90%    |
| Netzstandard *                                     | IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Luftfeuchtigkeit bei Lagerung               | 10 - 95%    |
| 10G-Unterstützung *                                | ✗  | Wärmeableitung                              | 89 BTU/h    |
| Auto MDI/MDI-X                                     | ✓  | Gewicht und Abmessungen                     |             |
| Ethernet LAN Datentransferraten                    | 100,1000 Mbit/s  | Breite                                      | 250 mm      |
|  |  | Tiefe                                       | 104 mm      |
|  |  | Höhe  | 27 mm       |
|  |  | Gewicht                                     | 730 g       |
| Datenübertragung                                   |  | Verpackungsdaten                            |             |
| Routing-/Switching-Kapazität *                     | 20 Gbit/s  | Verpackungsbreite                           | 228 mm      |
| Transferrate                                       | 14,88 Mpps   | Verpackungstiefe                            | 304 mm      |
| MAC-Adressentabelle *                              | 8000 Eintragungen  | Verpackungshöhe                             | 67 mm       |
| Jumbo Frames Unterstützung                         | ✓  | Paketgewicht                                | 1,97 kg     |
| Jumbo-Frames                                       | 9000   | Nachhaltigkeit                              |             |
| Datenpaket-Pufferspeicher                          | 0,256 MB   | Nachhaltigkeitskonformität                  | ✓           |
| Design   |  | Zertifikate                                 |             |
| Produktfarbe                                       | Schwarz  | Konformitätsbescheinigungen                 | RoHS        |
| LED-Anzeigen                                       | ✓  |   |             |
| Wandmontage  | ✓  |   |             |
| Anzahl Lüfter                                      | 0 Lüfter   |   |             |

| Leistungen                                       |             | Logistikdaten                     |            |
|--|-------------|-----------------------------------|------------|
| Mittlere Betriebsdauer zwischen Ausfällen (MTBF) | 1000070 h   | Ursprungsland                     | China      |
| <b>Energie</b>                                   |             | Breite des Versandkartons         | 323 mm     |
| Energiequelle *                                  | AC/DC       | Länge des Versandkartons          | 558 mm     |
| Netzteil enthalten *                             | ✓           | Höhe des Versandkartons           | 275 mm     |
| AC Eingangsspannung                              | 100 - 240 V | Warentarifnummer (HS)             | 85176990   |
| AC Eingangsfrequenz                              | 50 - 60 Hz  | Gewicht Versandkarton             | 13,7 kg    |
| DC input Spannung                                | 54 V        | Anzahl Produkte pro Versandkarton | 8 Stück(e) |
| Stromverbrauch (max.)                            | 156,1 W     |                                   |            |



4718937621187

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.