

ZYXEL

Zyxel GS1350-12HP-EU0101F Netzwerk-Switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grau

Marke : Zyxel

Artikel-Code: GS1350-12HP-EU0101F

Produktname : GS1350-12HP-EU0101F



Zyxel GS1350-12HP-EU0101F. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 10. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 24 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE.... Power over Ethernet (PoE). Rack-Einbau



Management-Funktionen		Sicherheit	
Switch-Typ *	Managed	Warteschleifenplanungs-Algorithmen	SPQ, WFQ, Weighted Round Robin (WRR)
Switch-Ebene	L2		
Web-basiertes Management	✓		
Konfiguration der Standorteinstellungen (CLI)	✓		
Systemereignisprotokoll	✓		
MIB Unterstützung	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113		
Anschlüsse und Schnittstellen		Multicast-Funktionen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	10	Multicast Unterstützung	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)		
Menge SFP-Modul-Steckplätze	2		
Netzwerk		Design	
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Rack-Einbau *	✓
10G-Unterstützung *	✗	Produktfarbe	Grau
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	LED-Anzeigen	✓
Port-Spiegelung	✓		
Unterstützung Datenflusssteuerung	✓		
Broadcast-Sturmkontrolle	✓		
		Leistungen	
		Geräuschpegel	27,3 dB
		Upgradefähige Firmware	✓
		Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1065025,45 h
		Energie	
		AC Eingangsspannung	100 - 240 V
		AC Eingangsfrequenz	50 - 60 Hz
		Stromverbrauch (max.)	160,3 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Anzahl Power over Ethernet (PoE) Anschlüsse	8
		Gesamtleistung Power over Ethernet (PoE)	130 W
		Betriebsbedingungen	
		Betriebstemperatur	-20 - 50 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C

Netzwerk		Betriebsbedingungen	
Spannbaum-Protokoll	✓	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
VLAN-Unterstützung	✓	Luftfeuchtigkeit bei Lagerung	5 - 95%
Virtuelle LAN-Funktionen	MAC address-based VLAN, Port-based VLAN	Wärmeableitung	546,62 BTU/h
Anzahl der VLANs	256	Gewicht und Abmessungen	
Lichtwellenleiter		Breite	267 mm
Ethernet-Kabel	1000BASE-X	Tiefe	162 mm
Verkablungstechnologie		Höhe	44 mm
		Gewicht	1,63 kg
Datenübertragung		Lieferumfang	
Routing-/Switching-Kapazität *	24 Gbit/s	Mitgelieferte Kabel	AC
Transferrate	17,8 Mpps	Rackmontageset	✓
MAC-Adressentabelle *	8000 Eintragungen	Logistikdaten	
Datenpaket-Pufferspeicher	0,525 MB	Warentarifnummer (HS)	85176990
Sicherheit			
DHCP-Funktionen	DHCP client, DHCP relay, DHCP snooping		
IGMP-Snooping	✓		
IGMP-Proxy	✓		
Unterstützte Sicherheitsalgorithmen	SNMP, SNMPv3, SSH, SSL/TLS		
MAC Adressen Filtern	✓		
Loop Protection	✓		



4718937604388

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-APR-2026. Prints or copies of Information are only valid on the printed Publication date