The TDC 22M PRO ATEX and TDC 30 PRO ATEX models are vacuum cleaners suitable for continuous use, 24/7, without the need for special maintenance. The main feature of these machines is their versatility of use, focusing on the suction of both dust and solids.

TDC 22M ATEX 22 MARKING TDC 30 ATEX 22 MARKING

→ II 3GD Ex dc h IIB T3 Gc - Ex h tc IIIC T 135°C Dc IP65

TECHNICAL FEATURES	TDC 22M 🕠	TDC 30 (.)
MODELS		
MOTORIZATION	Turbine	Turbine
POWER	2,2 kW	3 kW
VOLTAGE	230 V	400 V
FREQUENCY	50 Hz	50/60 Hz
AMPERAGE	16 A	6,7 A
AIR FLOW	320 m³/h	320 m³/h
DEPRESSION	200 mBar	250 mBar
MAX DEPRESSION	300 mBar	320 mBar
Ø NOZZLE	Tangential ø 60 mm	Tangential ø 60 mm
BODY DIAMETER	ø 460 mm	ø 460 mm
DIMENSIONS	85 x 65 x 199 cm	85 x 65 x 199 cm
WEIGHT	92 Kg	92 Kg
FILTERING SYSTEM	TDC 22M	TDC 30
FILTER TYPE	Cartridge	Cartridge
PRIMARY FILTER - SURFACE	22.000 cm ²	22.000 cm ²
FILTER MEDIA	M Conductive	M Conductive
SECONDARY FILTER	OPT - HEPA	OPT - HEPA
FILTER CLEANING	Semi Automatic Pneumatic Piston	Semi Automatic Pneumatic Piston
COLLECTION SYSTEM	TDC 22M	TDC 30
CAPACITY	100 Liters	100 Liters
LONGOPAC BARREL INTERCHANGEABILITY	YES	YES



steel



- Class M conductive aluminised cartridge primary filter, HEPA secondary filter
- Finned filter protection for reduced clogging



Semi-automatic cleaning system with pneumatic piston







Easy barrel release system

Longopac® continuous bag discharge system



