

SPECIFICATION



3.0mm



3.0mm: 6450g/m<sup>2</sup>



37 @ 300 x 300mm  
= 3.33m<sup>2</sup>



GENERAL PERFORMANCE

AS 1889.1  
EN 654



REACTION TO FIRE

EN ISO 9239 – 1 >8kw/m<sup>2</sup>



DIMENSION STABILITY

Dimensions/ Squareness/ Dimensional Stability:  
AS 1889.1



INDENTATION STABILITY

AS 1889.1



FLEXIBILITY

AS 1889.1



SLIP RESISTANCE

AS/NZS4586 Appendix D – R 9



APPLICATIONS

Polyflor VC Tile range is recommended as a cost effective flooring solution for public and commercial buildings e.g. supermarkets, retail stores, schools, commercial premises, storage areas etc. For further advice on specific applications consult Polyflor.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.

ISO 14001 ISO 9001

POLYFLOR AUSTRALIA PTY LTD.

59-65 WEDGEWOOD ROAD, HALLAM VIC. 3803, AUSTRALIA

PHONE: 1800 777 425 FAX: 03 9215 4444

E-MAIL: SALES@POLYFLOR.COM.AU WEB: WWW.POLYFLOR.COM.AU

POLYFLOR NEW ZEALAND.

100 PLUNKET AVE MANUKAU, AUCKLAND 2104, NEW ZEALAND

PHONE: 0800 765 935 FAX: 0800 846 737

E-MAIL: SALES@POLYFLOR.CO.NZ WEB: WWW.POLYFLOR.CO.NZ

POLYFLOR  
**VC TILE  
DELUXE RANGE**

Polyflor's Vinyl Composition Tile (VC Tile) range offers the following benefits:

- Economical flooring solution
  - Colourful aesthetics
  - 'Thru chip' pattern
  - Excellent durability
  - Minimal wastage

Polyflor VC Tile Deluxe Range.

Decoration and shade may vary slightly from the samples shown. The data presented is correct at the time of printing.