

**De Marque Collection**  
**Chevron Engineered Oak 90 x 600 x 21/6 mm.**

The stunning new De Marque Chevron Collection is now available with a contemporary palette of pre-finished colours. Our range provides wonderful warmth, charm and character delivering a truly unique renaissance appeal. Raw (un-coated) is also available for custom on-site finishing.

The Oak planks are manufactured from sustainable Real Oak timber combining a **6 mm solid Oak wear layer** engineered onto a 15 mm plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 21mm. It's perfectly suited for residential, multi-residential and commercial applications.

De Marque Chevron Collection		90 x 600 x 21/6 mm			
Colour	Scotia	Trim	Sqm/Ctn	Ctns/Pallet	Micro Bevel
Cannes	Limesmoke	Lugano	0.432	132	Yes 4 sides
Champagne	Wheat	Oak	0.432	132	Yes 4 sides
Dark Brown	Leysin	Walnut	0.432	132	Yes 4 sides
Mink Grey	Barrique	Champagne	0.432	132	Yes 4 sides
Raw ( un-coated)			0.432	132	Yes 4 sides
Semillon	Wheat	Oak	0.432	132	Yes 4 sides

**Parquetry Installation:** we recommend a full trowel spread adhesive bonded to a homogenous, flat and dry surface such as plywood. Wooden tongue inserts are provided to aid pattern design and assembly. **Parquetry is not suitable as a floating installation. For concrete slabs**, the slab must be dry <2.2% with full Moisture Barrier applied. The parquetry is then adhered with a matching brand elastomeric wood floor adhesive. Sika brand products are recommended.

**Key Features;** Engineered to exacting standards. Manufactured from environmentally sustainable resource. Extremely stable with excellent wear resistance. Wear layer can be refurbished and rejuvenated when required.

**Profile description;** Engineered Oak, Universal Tongue & Groove (1 side tongue/3 sides groove). **Micro Bevelled Edges.**

**Grade & Surface;** A/B/C/D Grade contains knots and split defects that are filled to compliment surface character. Pre-finished Matte, European PU coating. Light wire brush surface texture.

**Size & Length;** 90mm width, 600 mm length, 21mm thickness. 6mm Wear Layer.

**Slip Resistance;** In accordance with AS/NZS 4586-2013, P3. **VOC Emissions;** < E1, (Below World Health Organisation Levels)

**Fire Test Data;** AS/ISO9239.1.Critical Radiant Flux, 4.9kW/m2 Mean Smoke Development, 6 percent minutes.

For specification or reseller support contact, [www.preferencefloors.com.au](http://www.preferencefloors.com.au)

**Preference Floors (SA)**

ABN 63 600 454 215

27 Pambula Street,

Regency Park SA 5010

t +61 8 8268 8010

f +61 8 8268 8919

e [sa@preferencefloors.com.au](mailto:sa@preferencefloors.com.au)

**Preference Floors (QLD)**

ABN 81 169 158 990

6/268 Evans Road,

Salisbury QLD 4107

t +61 7 3875 1688

f +61 7 3875 1788

e [qld@preferencefloors.com.au](mailto:qld@preferencefloors.com.au)

**Preference Floors (VIC)**

ABN 34 151 422 927

19 Lanyon Street,

Dandenong South VIC 3175

t +61 3 9794 5111

f +61 3 9794 5133

e [vic@preferencefloors.com.au](mailto:vic@preferencefloors.com.au)

**Preference Floors (NSW)**

ABN 40 117 801 037

Unit A/31 Sturt Street,

Smithfield NSW 2164

t +61 2 9738 1188

f +61 2 9738 1199

e [sales@preferencefloors.com.au](mailto:sales@preferencefloors.com.au)