

De Marque Collection Herringbone Engineered Oak 120 x 600 x 21/6 mm.

The stunning new De Marque Herringbone Collection is now available with a Universal Tongue & Groove profile that enables multiple pattern assembly to create a number of different visuals. With a contemporary palette of pre-finished colours the range will provide wonderful warmth and charm to almost any interior. Raw (un-coated) available for custom on-site finishing.

The Oak planks are manufactured from sustainable Real Oak timber combining a **6 mm solid Oak wear layer** engineered onto a 15 mm plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 21mm. It's perfectly suited for residential, multi-residential and commercial applications.

De Marque Herringbone Collection			120 x 600 x 21/6 mm		
Colour	Scotia	Trim	Sqm/Ctn	Ctns/Pallet	Micro Bevel
Cabernet (same as Semillon)	Wheat	Oak	0.576m2	88	Yes 4 sides
Cognac (same as Aged Oak)	Rosybrown	Oak	0.576m2	88	Yes 4 sides
Raw (Un-coated)			0.576m2	88	Yes 4 sides
Riesling (same as Cannes)	Limesmoke	Silver	0.576m2	88	Yes 4 sides
Sauvignon (same as Champagne)	Wheat	Oak	0.576m2	88	Yes 4 sides
Vintage (same as Mink Grey)	Barrique	Champagne	0.576m2	88	Yes 4 sides

Parquetry Installation: we recommend a full trowel spread adhesive bonded to a homogenous, flat and dry surface such as plywood. Wooden tongue inserts are provided to aid pattern design and assembly. **Parquetry is not suitable as a floating installation. For concrete slabs,** the slab must be dry <2.2% with full Moisture Barrier applied. The parquetry is then adhered with a matching brand elastomeric wood floor adhesive. Sika brand products are recommended.

Key Features; Engineered to exacting standards. Manufactured from environmentally sustainable resource. Extremely stable with excellent wear resistance. Wear layer can be refurbished and rejuvenated when required.

Profile description; Engineered Oak, Universal Tongue & Groove (1 side tongue/3 sides groove). **Micro Bevelled Edges.**

Grade & Surface; A/B/C/D Grade contains knots and split defects that are filled to compliment surface character. Pre-finished Matte, European PU coating. Light wire brush.

Size & Length; 120mm width, 600 mm length, 21mm thickness. 6mm Wear Layer.

Slip Resistance; In accordance with AS/NZS 4586-2013, P3. **VOC Emissions;** < E1, (Below World Health Organisation Levels)

Fire Test Data; AS/ISO9239.1.Critical Radiant Flux, 4.9kW/m2 Mean Smoke Development, 6 percent minutes.



For specification or reseller support contact, www.preferencefloors.com.au

Preference Floors (SA)

ABN 63 600 454 215

27 Pambula Street,
Regency Park SA 5010

t +61 8 8268 8010

f +61 8 8268 8919

e sa@preferencefloors.com.au

Preference Floors (QLD)

ABN 81 169 158 990

6/268 Evans Road,
Salisbury QLD 4107

t +61 7 3875 1688

f +61 7 3875 1788

e qld@preferencefloors.com.au

Preference Floors (VIC)

ABN 34 151 422 927

19 Lanyon Street,
Dandenong South VIC 3175

t +61 3 9794 5111

f +61 3 9794 5133

e vic@preferencefloors.com.au

Preference Floors (NSW)

ABN 40 117 801 037

Unit A/31 Sturt Street,
Smithfield NSW 2164

t +61 2 9738 1188

f +61 2 9738 1199

e sales@preferencefloors.com.au