



## Specification

### Carpet Description

Cut Pile Twist

### Fibre Content

80% Wool 20% Synthetic

### Machine Gauge (AS2111.9)

31.5/10cm (1/8th)

### Finished Pile Height (AS2111.5)

8mm +/- 1mm

### Pile Weight (AS2111.11)

1630g/m (48 oz / yd )

### Primary Backing

Woven Polypropylene

### Secondary Backing

Jute

### Backing Adhesive

Synthetic Latex

### Carpet Width

3.66 metres (12ft)

### ACCS Registration

28091

### ACCS Grading

Contract Heavy Duty & Stairs  
Residential Extra Heavy Duty & Stairs

### Pattern Match

Not Applicable

### Flammability (ISO9239 - 1:2003)

Result - Mean 4.5 kw/m (Direct Stick)  
Smoke Value 750% min (Direct Stick)

### Tolerances

As per AS 1385 or +/- 5% whichever is greater

Specifications are subject to manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice.

As part of Feltex Carpets' continuous improvement program, Feltex Carpets reserves the right to change the specifications of or delete colours of this product without notice



Manufactured under a management system certified as complying with ISO 9001, ISO 14001 and AS 4801 by accredited certification bodies.

## General Instructions

• This carpet is manufactured and recommended for floor covering use only. Feltex Carpets does not assume any liability, real or implied, when carpet is applied otherwise.

• Feltex Carpets requires that all seams are sealed in the manner recommended by the manufacturer of the appropriate seam sealer.

• Walk off mats of sufficient size are recommended at building entryways to reduce soiling.

• Chair mats are recommended under chairs with castors, to preserve appearance retention and avoid premature wear.

### INSTALLATION

All carpet should be installed in accordance with Australian/NZ Standards Association Carpet Installation Recommendations AS/NZ2455-2007 and any other instructions/recommendations provided by Feltex Carpets unless otherwise specified.

### MAINTENANCE

Carpet should be cleaned and maintained in accordance with AS/NZS 3733/1995-1, and or as instructed by Feltex Carpets.

### COLOUR VARIATION

Shade or pattern may vary from sample and between dyelots and within production runs due to normal dyelot variation but will be within recognised textile industry standards. Colour appearance can also vary depending upon type of light under which a sample is viewed and the light sources where the carpet is installed.

### PERMANENT PILE REVERSAL (Shading / Puddling / Watermarking)

Light can play strange tricks with carpet, making it appear from certain angles that particular areas are lighter or darker than others. Known as shading, it is due to the pressure on the pile during use, causing pile to lay in different directions resulting in light refraction and is a feature characteristic of cut pile carpets (particularly solid colour). Apart from affecting appearance, it has no detrimental effect on the performance of the carpet.

### PATTERNED CARPETS

While Feltex Carpets uses the best available techniques to minimise pattern distortion during manufacture, the extensible nature of textile products means that some distortion due to shrinkage or stretch during and after manufacture is unavoidable, such that perfect pattern match cannot be guaranteed. Installation of patterned carpet will require more time, effort and skill and a competent carpet layer should be able to obtain a close pattern match in most circumstances though some irregularities may still be visible, particularly over multiple width installations. We further suggest you discuss pattern matching with your installer.

### PANELLING / PHASING

An effect known as phasing can occur where carpet design includes random use of contrasting colours when at times these colours can coincide in production. Similarly in loop pile carpets, shading effects of colour patterning can appear as panelling down the length of the carpet. Both phasing and panelling are an accepted part of the design and in no way affect the carpet's performance.

### SHIFT LINES

Construction of this carpet may involve the occurrence of shift lines across the width of the carpet. Colour, directional pile lay and light sources shining across the carpet may accentuate these lines in the form of shadowing. This is not a manufacturing fault and will not affect the carpet's wear or durability.

All product specifications and colourations are subject to normal manufacturing tolerances. As part of Feltex Carpets' continuous improvement program, Feltex Carpets reserves the right to change the specifications of or delete colours of this product without notice.



Feltex Commercial Carpets meet the Carpet Institute of Australia (CIA) environmental code of practice and indoor air quality standard for Low VOCs (Volatile Organic Compounds).



green building council australia  
MEMBER

Feltex Carpets Pty Ltd ACN 068 166 843  
T 1300 130 239 F 1800 654 595

Email commercial@feltex.com  
Web www.feltex.com

Sample Attached: 94/- Coal  
Sample Pictured: 93/- Fortress