

Technical

Country of Origin	Australia
Description	Patterned Level Loop Pile Carpet Tile
Colours	5 Standard Colours (plus 7 firm order only colours)
Yarn	100% Statron® Solution Dyed Nylon
Tile Thickness	6.5 mm (tolerance ±1mm)
Pile Weight	580g/m ² (17oz/yd ²)
Gauge	47.2/10cm (1/12 th gauge)
Backing Structure	Enviro Bac® - Minimum of 60% recycled content
Tile Size	500mm x 500mm
Availability Options	1000mm x 500mm - Planks [^] 1000mm x 250mm - Skinny Planks [^] Enviro Bac Plus® - Cushion Backed Easy Grip™ - Adhesive Free Installation
Installation Method	1/4 Turn - Brick - Directional

Performance

Anti-Static	AATCC 134 <3.5 Kilovolts at 21°C & 20% Relative Humidity
Flammability (AS ISO 9239.1.2003)	CRF 7.8kW/m ² [†] Smoke Value 412% Minutes
Colourfastness to Light	6-7 (Minimum mandatory performance requirement for ACCS:5)
Light Reflectance Values	Available Upon Request
Stain Treatment	Stain Warden®
Biocontaminant Control	Bioshield® Antimicrobial Treatment
ACCS Rating	Contract Heavy & Duty & Stairs #28194 [†]
Warranty	12 Year*

Sustainability

PVC Minimisation	100% PVC Free
Recycled Content	Minimum of 60% recycled content in backing structure Minimum of 40% recycled content by weight of product
Indoor Air Quality	Green Building Council & Green Label Plus compliant for VOC's emission rate limits [†]
Product Stewardship	This product is RECYCLABLE and qualifies for take back at the end of life under the Godfrey Hirst Product Stewardship Program.
Green Star	Environmental Certification Scheme (ECS) Level 4 Maximum points - Certification #28194 [†]
Accreditation	Manufactured under a quality, environmental and health and safety system certified and complying with ISO9001, ISO14001 and AS4801 by an accredited certification body.

meets
Green Label Plus
specifications



green building council australia
MEMBER



www.intlcert.com

HEAD OFFICE

Geelong

7 Factories Rd,
South Geelong, VIC 3220 Australia
Fax +61 (0) 3 5222 3885

1300 444 778

general.enquiries@godfreyhirst.com

www.godfreyhirst.com

SALES OFFICES

Melbourne

2 Gilbertson Rd,
Laverton North, VIC 3026

Sydney

28 Percival Rd,
Smithfield, NSW 2164

Brisbane

33 Gassman Dr,
Yatala, QLD 4207

Adelaide

8 Ware St,
Thebarton, SA 5031

Perth

Unit 1 / 5 Leeway Crt
Osborne Park, WA 6017

INTERNATIONAL OFFICES

New Zealand

FREECALL (NZ): 0800 500 210

Auckland Office

142 Kerrs Rd, Wiri
Manukau City, 2104
Auckland, New Zealand
Ph +64 (0) 9 268 3300

Wellington Office

C/- Canterbury Spinners
6 Bell Road South
Lower Hutt, Wellington

Christchurch Office

Unit 3, 9 Craft Place
Middleton, Christchurch

Singapore

200 Jalan Sultan #10/07 Textile Centre,
Singapore, 199018.
Ph +65 6841 5529

Specifications and colourations are subject to nominal manufacturing tolerances. As part of Godfrey Hirst's continuous improvement program, Godfrey Hirst reserves the right to change specifications of of delete colours of this product without notice.

All Godfrey Hirst carpet tile products must be installed in accordance with AS2455 (Parts 1 & 2) and the Godfrey Hirst Carpet Tile Installation Instructions.

*Production time may vary depending on size of production run.

†Warranty terms and conditions apply.

‡Test results and certificates are available on request.

