

**Technical**

Country of Origin	Australia
Description	Patterned Cut & Loop Pile Carpet Tile
Yarn	100% BCF Nylon
Colours	12 Standard
Tile Thickness	7.0 mm (tolerance ±1mm)
Pile Weight	750g/m <sup>2</sup> (22oz/yd <sup>2</sup> )
Gauge	47.2/10cm (1/12 <sup>th</sup> gauge)
Backing Structure	Enviro Bac® - Minimum of 60% recycled content
Tile Size	500mm x 500mm
Availability Options	1000mm x 500mm - Planks <sup>^</sup> 1000mm x 250mm - Skinny Planks <sup>^</sup> Enviro Bac Plus® - Cushion Backed Easy Grip™ - Adhesive Free Installation
Installation Method	1/4 Turn - Brick - Ashlar

**Performance**

Anti-Static	AATCC 134 <3.5 Kilovolts at 21°C % 20% Relative Humidity
Flammability (AS ISO 9239.1.2003)	CRF 8.5kW/m <sup>2</sup> <sup>†</sup> Smoke Value 188% Minutes
Colourfastness to Light	6-7 (Minimum mandatory performance for ACCS:5)
Light Reflectance Values	Available Upon Request
Stain Treatment	Stain Warden®
Biocontaminant Control	Bioshield® Antimicrobial Treatment
ACCS Rating	Contract Extra Heavy & Duty & Stairs #12129 <sup>†</sup>
Warranty	15 Year*

**Sustainability**

PVC Minimisation	100% PVC Free
Recycled Content	Minimum of 60% recycled content in backing structure Minimum of 40% recycled content by weight of product
Indoor Air Quality	Green Building Council & Green Label Plus compliant for VOC's emission rate limits <sup>†</sup>
Product Stewardship	This product is RECYCLABLE and qualifies for take back at the end of life under the Godfrey Hirst Product Stewardship Program
Green Star	Environmental Certification Scheme (ECS) Level 4 Maximum points - Certification #12129 <sup>†</sup>
Accreditation	Manufactured under a quality, environmental and health and safety system certified and complying with ISO9001, ISO14001 and AS4801 by an accredited certification body.

**HEAD OFFICE**

**Geelong**

7 Factories Rd,  
South Geelong, VIC 3220 Australia  
Fax +61 (0) 3 5222 3885

**1300 444 778**  
[general.enquiries@godfreyhirst.com](mailto:general.enquiries@godfreyhirst.com)  
[www.godfreyhirst.com](http://www.godfreyhirst.com)

**SALES OFFICES**

**Melbourne**

2 Gilbertson Rd,  
Laverton North, VIC 3026

**Sydney**

28 Percival Rd,  
Smithfield, NSW 2164

**Brisbane**

33 Gassman Dr,  
Yatala, QLD 4207

**Adelaide**

8 Ware St,  
Thebarton, SA 5031

**Perth**

Unit 1 / 5 Leeway Cr  
Osborne Park, WA 6017

**INTERNATIONAL OFFICES**

**New Zealand**

**FREECALL (NZ): 0800 500 210**

**Auckland Office**

142 Kerrs Rd, Wiri  
Manukau City, 2104  
Auckland, New Zealand  
Ph +64 (0) 9 268 3300

**Wellington Office**

C/- Canterbury Spinners  
6 Bell Road South  
Lower Hutt, Wellington

**Christchurch Office**

Unit 3, 9 Craft Place  
Middleton, Christchurch

**Singapore**

200 Jalan Sultan #10/07 Textile Centre,  
Singapore, 199018.  
Ph +65 6841 5529

Specifications and colourations are subject to nominal manufacturing tolerances. As part of Godfrey Hirst's continuous improvement program, Godfrey Hirst reserves the right to change specifications of of delete colours of this product without notice.

All Godfrey Hirst carpet tile products must be installed in accordance with AS2455 (Parts 1 & 2) and the Godfrey Hirst Carpet Tile Installation Instructions.

<sup>†</sup>Production time may vary depending on size of production run.

<sup>†</sup>Warranty terms and conditions apply.

<sup>†</sup>Test results and certificates are available on request.

