

Head Office

7 Factories Road
 South Geelong 3220
 Victoria Australia
 Email: gfirst@godfreyhirst.com
 www.godfreyhirst.com

Postal Address

PO Box 93
 Geelong 3220
 Victoria Australia
 Telephone: +61 (3) 5225 0222
 Facsimile: +61 (3) 5222 3885

PRODUCT : **NETCORP 40oz**

DESCRIPTION	:	Needlepoint Graphic Loop
FIBRE TYPE	:	100% Selected carpet wools averaging not finer than 33 micron (Tolerance \pm 5.0%)
YARN CONSTRUCTION	:	Multi-Ply Woollen Spun
TOTAL PILE WEIGHT	:	1360 gms/m ² - 40 oz/yd ² (Tolerance \pm 5.0%)
PILE HEIGHT	:	5.0 mm (Tolerance \pm 1.0mm)
MACHINE GAUGE	:	63.0 per 100 mm - 1/16th gauge
WIDTH	:	366 cm
PRIMARY BACKING	:	Spun Bonded Polypropylene
LATEX	:	Synthetic
SECONDARY BACKING	:	Jute
A.C.C.S. RATING	:	Contract Heavy Duty & Stairs Residential Extra Heavy Duty & Stairs Registration No. 22061
RADIANT HEAT SOURCE AS ISO 9239.1.2003	:	CHF 8.3 kW/m ² [conventional] Smoke Value 80% min
INDOOR AIR QUALITY	:	Total Volatile Organic Compounds (TVOC's) Emission level test results for this product comply with Green Label Plus criteria and Green Building Council requirements. (test results are available on request)
EXTRACTABLE MATTER Dichloromethane Extract A.S. 2001.3.4	:	1.5% Maximum
RESISTANCE TO INSECT PESTS A.S. 2001.6.1	:	Pass
TUFT WITHDRAWAL FORCE A.S. 2111.15	:	30 Newtons (minimum)
SECONDARY BACKING ADHESION A.S. 2111.16	:	40 Newtons (minimum)
COLOUR FASTNESS TO LIGHT B.S. 1006.B02	:	5-6
COLOUR FASTNESS TO SHAMPOO A.S. 2111.19.2	:	3-4 minimum
COLOUR FASTNESS TO RUBBING A.S. 2111.19.1	:	3-4 [medium to light shades] 3 [dark shades]

www.godfreyhirst.com

When buying carpet always insist on an ACCS rated carpet.