

**Head Office**

7 Factories Road  
 South Geelong 3220  
 Victoria Australia  
 Email: gfirst@godfreyhirst.com  
 www.godfreyhirst.com

**Postal Address**

PO Box 93  
 Geelong 3220  
 Victoria Australia  
 Telephone: +61 (3) 5225 0222  
 Facsimile: +61 (3) 5222 3885

**PRODUCT**
**TUCSON**

<b>DESCRIPTION</b>	:	Level Loop Pile
<b>YARN CONSTRUCTION</b>	:	100% Statron™ Solution Dyed Nylon
<b>TOTAL PILE WEIGHT</b>	:	575 gms/m <sup>2</sup> - 17 oz/yd <sup>2</sup> (Tolerance ±5.0%)
<b>PILE HEIGHT</b>	:	3.0 mm (Tolerance ± 1mm)
<b>MACHINE GAUGE</b>	:	47.2 per 100 mm – 1/12th gauge
<b>PRIMARY BACKING</b>	:	Woven Polypropylene
<b>SECONDARY BACKING</b>	:	Jute [optional Synthetic]
<b>WIDTH</b>	:	3.66 mts [broadloom]
<b>ACCS ENVIRONMENTAL CLASSIFICATION SCHEME</b>	:	Graded - Contract Heavy Duty and Stairs Environmental Certification No 28102
<b>INDOOR AIR QUALITY</b>	:	Complies with Green Building Council and Green Label Plus requirements for VOC emission levels
<b>ANTISTATIC</b>	:	Permanent Conductive Fibre < 3.0 kV at 21oC and 20% relative humidity
<b>RADIANT HEAT SOURCE ASISO 9239.1-2003</b>	:	CHF Value 3.7 kW/m <sup>2</sup> [Direct Stick] Smoke Value 83 % min
<b>STAIN PROTECTION IWS 282-1992</b>	:	StainWarden™ 4
<b>EXTRACTABLE MATTER Dichloromethane Extract A.S. 2001.3.4</b>	:	1.0% Maximum
<b>RESISTANCE TO INSECT PESTS A.S. 2001.6.1</b>	:	Pass
<b>TUFT WITHDRAWAL FORCE A.S. 2111.15</b>	:	30 Newtons (minimum)
<b>SECONDARY BACKING ADHESION A.S. 2111.16</b>	:	30 Newtons (minimum)
<b>COLOUR FASTNESS TO LIGHT B.S. 1006.B02</b>	:	5-6 (minimum)
<b>COLOUR FASTNESS TO SOLVENTS A.S. 2001.4.16</b>	:	4-5
<b>COLOUR FASTNESS TO SHAMPOO A.S. 2111.19.2</b>	:	3-4
<b>COLOUR FASTNESS TO RUBBING A.S. 2111.19.1</b>	:	3-4
<b>COLOUR FASTNESS TO BLEACHING A.S. 2001.4.11</b>	:	4-5
<b>COLOUR FASTNESS TO WATER A.S. 2001.4.8</b>	:	4-5