









Creamsource_SKY V3.indd 1 29/3/19 8:14 pm



SK

3200K





CREAMSOURCE

Unit 6, 888 Bourke St Zetland, NSW 2017, AUSTRALIA


SALES HOTLINE
TEL (SYD): +61 2 9699 8688
TEL (USA): +1 818 748 8401
sales@creamsource.com
www.creamsource.com

Spectral Output at 3200K





1253 lx



Creamsource Sky is the original high power full spectrum softsource, combining the latest LED technology with sophisticated colour management, modern ergonomics and stunning design.

At Sky's heart is an array of six powerful LED Engines, cooled by a highly efficient and silent heatpipe system. Colour temperature is continously adjustable from 2,200K to 15,000K with similtaneous adjustment of the green/ magenta axis. Hue and saturation controls mean you're not just limited to white light either – any colour is possible. In addition, the Creamsource Sky is able to deliver an incredibly wide and even beam in a compact package, allowing better utilisation of limited studio space. Rain set? No problem. Stormy weather exterior, or just too much dust? With IP65 rating the Sky has you covered.

Welcome to the age of lighting built exclusively to harness your creativity.

Colour Quality

The LED engines have been optimised for excellent colour reproduction, with a typical CRI of 95 between the ranges of 3200K and 6500K. Light output is smoothly homogonised with no multiple shadows or colour fringing.

Product Specifications

Maximum Ambient 40°C Temperature

Cooling Passive (Silent)
Estimated LED 50,000hrs

Lifespan (L70)

Input (Head) 48V DC, Max 25A, 1200W

 Input (Power Supply)
 90-260V AC, 50-60Hz, Max 14A

 Weight
 23kg / 50lbs (head), 12kg / 26lbs

(power supply)

Dimensions 940mm x 200mm / 37" x 8" (head)

Protection Class IP65

Beam Angle 115 degrees

Warranty 5 year warranty on registered fixtures, 12 months on accessories

Features at a glance

- 1200W of LED power providing the equivalent output to a 5K Tungsten
- Superb colour rendition with typical CRI of 95 from 3200K to 6500K
- Full colour temperature adjustment from 2,200K to 15,000K with a full stop of Green/Magenta control
- Hue and Saturation settings, plus direct RBGAW capability
- Smooth dimming with high speed capability
- Removable power supply with quick release mechanism
- DMX via standard 5-pin XLR connectors
 SHoWDMX Wireless DMX built in
- Water resistant design (IP65)
- Accepts industry standard diffusion skirts
- Onboard control keypad and OLED display



