

© CURT **FOCKERBALL™ TRAILER BALL**

SHOCKDROP[™] TECHNOLOGY.

ENHANCED COMFORT. IMPROVED CONTROL.


Retrofits most ball mounts to improve towing experience



The RockerBall[™] is a dynamic trailer ball featuring ShockDrop[™] technology. It can be bolted onto a standard ball mount to provide increased comfort, control and confidence.


- Cushioned isolators reduce rattling and vibration for a more comfortable ride
- Reduces shock loads to the vehicle during sudden braking or acceleration
- Minimizes stress on tow vehicle's suspension and brakes for extended longevity
- Anti-swivel base keeps RockerBall[™] locked in place
- Virtually maintenance-free with no airbag or bearings to service
- Forged steel construction for dependable towing power
- Durable carbide black powder coat finish on base and chrome plating on ball
- Tested for safety to meet SAE J684 specifications
- Not compatible with Rebellion[™] XD ball mount

Enhanced comfort.



Unlike a metal-on-metal connection, ShockDrop[™] absorbs unevenness in the road to maximize your comfort

Improved control.



ShockDrop[™] dynamically reacts to jarring, limiting its effects and giving the driver increased control on the road





ROCKERBALL[™] TRAILER BALLS & STARTER KITS














40249

Shank Diameter (C)	Shank Length (B)	Rise (D)	Tongue Width (E)	GTW	Pkg Box#	Pkg Throne#			
2" Ball Diameter (A)									
3/4"	2-1/8"	1-1/2"	2"	3,500 lbs.		40246			
1"	2-1/8"	1-1/2"	2-1/2"	7,500 lbs.	40047	40247			
2-5/16" Ball Diameter (A)									
1"	2-1/2"	1-5/8"	2-1/2"	7,500 lbs.		40248			
1-1/4"	2-7/8"	1-5/8"	3"	12,000 lbs.		40249			



A: Ball diameter B: Shank length C: Shank diameter D: Rise E: Tongue width







Part#	Shank Size	GTW / TW	Ball Diameter	Drop	Length	Included Parts
45143	2"	7,500 / 750 lbs.	2"	3"	8-1/4"	45050 ball mount, 40047 RockerBall [™] , 22321 anti-rattle hitch pin
45144	2"	7,500 / 750 lbs.	2"	5"	9-1/4"	45070 ball mount, 40047 RockerBall [™] , 22321 anti-rattle hitch pin