



Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

Identification	tion
· Product id	entifier
	e: First Street Butane Fuel de: 62609 (F305)
Recommen	ded use and restriction on use ded use: Fuel s on use: Contact manufacturer/supplier
• Manufactur Fancyheat C 40 Veronica	Corporation Avenue J 08873 USA
CHEMTREC 1-800-424-9	telephone number: ; 300 (US/Canada) /-3887 (International)
! Hazard(s)	identification
Classificat	ion of the substance or mixture
Flam. Gas 1	
Flam. Gas 1 Press. Gas Simple Asph	 H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.
Flam. Gas 1 Press. Gas Simple Asph Label elem GHS label e The product Hazard pict	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Ments lements is classified and labeled according to the Globally Harmonized System (GHS). ograms:
Flam. Gas 1 Press. Gas Simple Asph • Label elem • GHS label e The product	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Ments lements is classified and labeled according to the Globally Harmonized System (GHS). ograms:
Flam. Gas 1 Press. Gas Simple Asph Label elem GHS label elem Hazard pict Hazard pict GHS02 GHS Signal word Hazard stat H220 Extren H280 Contai May displace	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Ments lements is classified and labeled according to the Globally Harmonized System (GHS). ograms: 04 I: Danger ements: hely flammable gas. ns gas under pressure; may explode if heated. e oxygen and cause rapid suffocation. ary statements:
Flam. Gas 1 Press. Gas Simple Asph • Label elem • GHS label e The product • Hazard pict • Hazard pict • GHS02 GHS • Signal word • Hazard stat H220 Extrem H280 Contai May displace • Precautiona P210 P377 P381	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Ments lements is classified and labeled according to the Globally Harmonized System (GHS). ograms: 04 I: Danger ements: hely flammable gas. ns gas under pressure; may explode if heated. e oxygen and cause rapid suffocation.

FancyHeat

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Trade name: First Street Butane Fuel

Revision: 11/17/2018

(Cont'd. of page 1)

There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Compon	· Components:		
106-97-8	butane	 Flam. Gas 1, H220 Press. Gas, H280 	50-100%
75-28-5	isobutane	 Flam. Gas 1, H220 Press. Gas, H280 	25-50%
74-98-6	propane	 Flam. Gas 1, H220 Press. Gas, H280 	2.5-10%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. • After skin contact: Wash with soap and water. If skin irritation is experienced, consult a doctor. · After eye contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: Unlikely route of exposure. Rinse out mouth and then drink plenty of water. Do not induce vomiting: immediately call for medical help. Most important symptoms and effects, both acute and delayed: Headache Breathing difficulty Coughing Dizziness Unconsciousness · Danger: Danger of impaired breathing. May displace oxygen and cause rapid suffocation. Indication of any immediate medical attention and special treatment needed: If necessary oxygen respiration treatment.

(Cont'd. on page 3)

FancyHeat

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Trade name: First Street Butane Fuel

Revision: 11/17/2018

(Cont'd. of page 2)

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

• Extinguishing media Suitable extinguishing agents: Fire-extinguishing powder BC powder · For safety reasons unsuitable extinguishing agents: Water • Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. Danger of receptacles bursting because of high vapor pressure if heated. Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. Additional information: Eliminate all ignition sources if safe to do so. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. 6 Accidental release measures Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Use personal protective equipment as required. Keep away from ignition sources. Protect from heat. Environmental precautions Avoid release to the environment. Methods and material for containment and cleaning up Absorb liquid components with liquid-binding material. Allow gas to dissipate. Send for recovery or disposal in suitable receptacles. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

[.] Handling

· Precautions for safe handling:

- Open and handle receptacle with care. Use only in well ventilated areas.
- Keep out of reach of children.

(Cont'd. on page 4)



Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

rade name: First Street Butane Fuel	
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Emergency cooling must be available in case of nearby fire. Flammable gas-air mixtures may be formed in empty containers/receptacles. Keep respiratory protective device available. 	(Cont'd. of page 3)
 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame. Observe official regulations on storing packagings with pressurized containers. Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents. Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Keep containers tightly sealed. Specific end use(s) No relevant information available. 	

8 Exposure controls/personal protection

· Components w	ith limit values that require monitoring at the workplace:	
106-97-8 butan)	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm	
TLV (USA)	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX	
EL (Canada)	Short-term value: 750 ppm Long-term value: 600 ppm	
EV (Canada)	Long-term value: 800 ppm	
LMPE (Mexico)	Long-term value: 1000 ppm	
75-28-5 isobuta	ne	
TLV (USA)	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX	
EV (Canada)	Long-term value: 800 ppm	
LMPE (Mexico)	Long-term value: 1000 ppm	
74-98-6 propan	9	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	refer to Appendix F inTLVs&BEIs book; NIC-EX	
EL (Canada)	Long-term value: 1000 ppm	
EV (Canada)	Long-term value: 1000 ppm	
LMPE (Mexico)	Long-term value: 1000 ppm	

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

Trade name: First Street Butane Fuel

(Cont'd. of page 4)

Exposure controls
Personal protective equipment:
General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
Engineering controls: Use only outdoors or in a well-ventilated area.
Breathing equipment: Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

- Protection of hands: Gloves should provide protection from freezing temperatures.
- Eye protection:



Tightly sealed goggles

· Body protection: Not required under normal conditions of use.

- · Limitation and supervision of exposure into the environment
- Avoid release to the environment.

Information on basic physical a	and chemical properties
Appearance: Form:	Compressed gas
Color:	Colorless
Odor:	Odorless
Odor threshold:	Not determined.
pH-value: Melting point/Melting range:	Not determined. -137.99/-160 °C (-216/-256 °F) (Butane/Isobutane) -188 °C (-306 °F) (Propane)
Boiling point/Boiling range:	-11 °C (12 °F)
Flash point:	<0 °C (<32 °F)
Flammability (solid, gaseous):	Extremely flammable liquefied gas.
Auto-ignition temperature:	365 °C (689 °F)
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits	
Lower:	1.5 Vol %
Upper:	8.5 Vol %





acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Trade name: First Street Butane Fuel

Revision: 11/17/2018

	(Cont'd. of page 5
Oxidizing properties:	Not determined.
· Vapor pressure at 25 °C (77 °F):	1820 mmHg
Density:	
Relative density at 20 °C (68 °F):	0.55 g/cm ³ (4.59 lbs/gal)
Vapor density at 20 °C (68 °F):	2.3/2.01/1.52 g/cm ³ (19.194/16.773/12.6 lbs/gal) (Butane
(iii)	Isobutane/Propane)
	air = 1
Evaporation rate:	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No relevant information available.

10 Stability and reactivity

· Reactivity: No relevant information available.

• Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

[•] Possibility of hazardous reactions

Develops readily flammable gases / fumes.

Reacts with oxidizing agents.

Reacts with peroxides.

Reacts with halogenated compounds.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

· **Incompatible materials** Oxidizing agents

Hazardous decomposition products Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.

• On the eye: Based on available data, the classification criteria are not met.

(Cont'd. on page 7)



acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

Trade name: First Street Butane Fuel

	(Cont'd. of page
Sensitization: Based on available data, the classification criteria are not met.	
IARC (International Agency for Research on Cancer):	
None of the ingredients are listed.	
NTP (National Toxicology Program):	
None of the ingredients are listed.	
OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	
 Probable route(s) of exposure: Inhalation. Eye contact. Skin contact. Acute effects (acute toxicity, irritation and corrosivity): May displace oxygen and cause rapid suffocation. Repeated dose toxicity: No relevant information available. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met. 	

12 Ecological information

[·] Toxicity

- · Aquatic toxicity No relevant information available.
- Persistence and degradability No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid transfer into the environment.
- [•] Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

(Cont'd. on page 8)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Trade name: First Street Butane Fuel

Revision: 11/17/2018

(Cont'd. of page 7)

• Uncleaned packagings
 • Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1075
UN proper shipping name DOT, IATA ADR, IMDG	Petroleum gases, liquefied PETROLEUM GASES, LIQUEFIED
Transport hazard class(es)	
DOT	
•	
Class	2.1
Label	2.1
ADR	
Class	2 1F Gases
Label	2.1
IMDG, IATA	
Class Label	2.1 2.1
Packing group	This UN-number is not assigned a packing group.
Environmental hazards	This on-number is not assigned a packing group.
Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Gases 23 F-D,S-U
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.



FancyHeat

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

Trade name: First Street Butane Fuel

(Cont'd. of page 8)

• Transport/Additional information:

· IATA

Ca

Cargo Aircraft Only.

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

· United States (USA)

· SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

• TSCA (Toxic Substances Control Act)

All ingredients are listed.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

106-97-8	butane	10000
75-28-5	isobutane	10000
74-98-6	propane	10000

Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

• EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

(Cont'd. on page 10)



acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/17/2018

Revision: 11/17/2018

Trade name: First Street Butane Fuel

(Cont'd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed.

* Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 11/17/2018 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LDLo: Lowest Lethal Dose Observed

Flam. Gas 1: Flammable gases – Category 1

Press. Gas: Gases under pressure – Compressed gas

Sources

Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com