Sun King Torch SK-781 Greenlight Planet Inc. Results based on test procedures detailed in IEC 62257-9-5 v.4

Verify online: https://data.verasol.org/products/sek/glp-Sk781 Valid until: December 31, 2022



Meets the Lighting Global Pico-PV Quality Standards



Light point(s)



Plug-and-play



## WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system

## PERFORMANCE DETAILS

Setting	Description	Total light output (lumens)	
Turbo	LED on highest lighting setting consuming 3.3 W of power without the diffuser.	270 lumens	
Normal	LED on highest lighting setting consuming 1.0 W of power without the diffuser.	not tested	
Strobe	LED on highest lighting setting consuming 0.39 W of power without the diffuser.	not tested	

Performance measure	Brightness setting: Turbo			
	2.9			
	Brightness setting: Normal			
Lighting full battery run time (hours)	9.5			
	Brightness setting: Strobe			
	25			

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (Im)	Lumen efficacy* (Im/W)	CRI**	CCT***	Distribution type	Lumen maintenance****
SK781 integrated torch light	1	3 diffus	Turbo (without diffuser)	270	80	73	7000	Narrow	99%
			Turbo (with diffuser)	240	73	73	6900	Wide	35 <sup>7</sup> 0

<sup>\*</sup>Lumen efficacy is the power consumption at a light point during the light output test.

\*\*Color Rendering Index. An index of 100 is equivalent to vieiwing objects in daylight; above 80 is considered good.

\*\*\*Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

\*\*\*\*Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES						
LEDs   UV-free LEDs are used to optimize		e health and safety as well as efficiency.				
DURABILITY						
Overall durability and workmanship		Pass				
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection.				
Level of water protection	Solar torch	Has protection from frequent rain; met IPX3				
MAIN UNIT BATTERY DETAILS						
Battery replaceability		Not easily replaceable with common tools.				
Battery chemistry		Lithium-ion				
Battery package type		18650				
Battery capacity		2.6 Ah				
Battery nominal voltage		3.7 V				
Battery status indication		One indicator shows the charging status.				
MARKS AND CERTIFICATIONS						
Factory certification						
Safety certification						
Other certification						
PRODUCT DETAILS						
Manufacturer name		Greenlight Planet Inc.				
Product name		Sun King Torch				
Product model / ID number		SK-781				
Contact information		care@greenlightplanet.com				
Website		www.greenlightplanet.com				
Dimensions (entire product in package)		3.4 x 3.4 x 14 cm				
Mass		135 g				
SSS INFORMATION						
Specs sheet expiration date		December 31, 2022				
Quality standards framework version		2020				
Revision		2020.07				