

Sun King Boom

SK-321
Greenlight Planet

Results based on test procedures detailed in
IEC 62257-9-5 v.4

Verify online:

www.lightingglobal.org/products/glp-skboom

Valid until: October 31, 2021



Meets the Lighting Global Pico-PV Quality Standards



Mobile charging

1

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system.

PERFORMANCE DETAILS

	Appliance ^a	Description	Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
			Used alone ^b	Used in combination ^c
included in kit	Integrated Lamp	One light point totalling 170 lumens on Turbo and 1.2 W	6.6 hours	2.9 hours
	Integrated Radio	integrated radio that consumes 0.42 W while in-use.	21 hours	2.2 hours
sold separately	Mobile phone	Basic phone (3.7 Wh battery)	1.5 full charge(s)	0.75 full charge(s)

Available daily electrical energy^c (Wh/day) 8

Performance measure	Brightness setting: Turbo
Lighting full battery run time ^d for main unit (hours)	6.6
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any auxiliary lights included with the product)	1090

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS

Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
Integrated lamp	1	3	Turbo	170	130	72	5000	Wide	100%
			Low	27	130	72	4900		

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES**Enclosure****Made from ABS and polycarbonate plastic****PORTS****1****USB 2.0 type A**

Mobile phones can be charged. Adapters are included.

DURABILITY

Overall durability and workmanship

Pass

Durability tests passed

Switch test, Drop test, Strain relief test, physical ingress protection.

Level of water protection

Main Unit

has protection from occasional rain; met with appropriate warning label

PV module

Has protection from permanent outdoor exposure.

SOLAR DETAILS

PV module type

Polycrystalline silicon

PV maximum power

2.6 watts

BATTERY DETAILS

Battery replaceability

Not easily replaceable with common tools.

Battery chemistry

Lithium iron phosphate

Battery package type

Cylindrical 26650

Battery capacity

3.3 Ah

Battery nominal voltage

3.3 V

Battery status indication

Five indicators for battery state of charge.

PRODUCT DETAILS

Manufacturer name

Greenlight Planet

Product name

Sun King Boom

Product model / ID number

SK-321

Contact information

sales@greenlightplanet.com

Website

www.greenlightplanet.com

Dimensions (entire product in package)

20.5 x 14 x 9 cm

Mass

860 g

SSS INFORMATION

Specs sheet expiration date

October 31, 2021

Quality standards framework version

2019

Revision

2019.08