

VeraSol

Standardized Specifications Book

Manufacturer: Beebeejump Technology

Component Family Name: P1L Family

Date of Standardized Specifications Book Expiration: September 30, 2025

Verify Online: <https://data.verasol.org/products/sek/bbj-p1l-family>

Contact Information: info@beebeejump.com

Website: www.beebeejump.ng



This VeraSol Standardized Specifications Book presents a **component-level Standardized Specifications Sheet** listing the available components in the product family by component type, each individual component's performance rating, and performance results for each component tested according to the Edition 4 of IEC 62257-9-5. Following the component-level Standardized Specifications Sheet is a **list of the systems** covered by this Specifications Book that use combinations of these components.

NOTICE: Systems or kits developed using components from the component family will each perform differently and have not all been evaluated on a system-level basis. All systems listed in this Specifications Book are regarded to have passed IEC TS 62257-9-8.

Quality Standards Framework Version: 2023

Revision: 2025.08

Component-Level Standardized Specifications Sheet

Beebeejump Technology

P1L Family

Battery / Control Box

Name / Model Number	Battery Chemistry	Nominal Voltage (V)	Battery Capacity Rating (mAh)	Measured Battery Capacity (mAh)
Main unit with 6.4 Ah battery	Lithium iron phosphate	6.4	6400	6500

PV Module

Name / Model Number	Peak Power at STC Rating (W)	Measured Peak Power at STC (W)
10 W poly-si PV	10	8.6
10 W mono-si PV	10	11
15 W poly-si PV	15	14
15 W mono-si PV	15	not tested
20 W poly-si PV	20	18
20 W mono-si PV	20	18

Light Sources*

Name / Model Number	Luminous Flux Rating (lm)				Measured Luminous Flux (lm)				Measured Lamp Efficacy (lm/W)			
	high	bright	medium	low	high	bright	medium	low	high	bright	medium	low
1.5 W LED - 2 Setting	--	110	--	--	--	140	--	40	--	100	--	140
1.5 W LED- 3 Setting	110	--	--	--	140	--	110	--	98	--	110	--

*Light points and appliances may perform differently when used with different systems.

NOTICE: As indicated, not all components listed on this page were tested according to the Quality Test Method (QTM) in Edition 4 of IEC 62257-9-5. However, based on the satisfactory performance of the tested components in the family, the components that were not tested are regarded to have passed IEC TS 62257-9-8:2020. In addition, all tested components passed an internal inspection, the full array of applicable QTM durability tests, as well as ingress protection testing (where applicable).

List of Covered Systems

Beebeejump Technology

P1L Family

System Name	Number of each component included in each system								
	Main unit with 6.4 Ah battery	1.5 W LED - 2 Setting	1.5 W LED- 3 Setting	10 W poly-si PV	10 W mono-si PV	15 W poly-si PV	15 W mono-si PV	20 W poly-si PV	20 W mono-si PV
P1L E03-10 **	1	3	--	--	--	--	--	--	--
P1L E03-15	1	3	--	--	--	1	--	--	--
P1L E03-20	1	3	--	--	--	--	--	1	--
P1L E04-10	1	4	--	1	--	--	--	--	--
P1L E04-15	1	4	--	--	--	1	--	--	--
P1L E04-20	1	4	--	--	--	--	--	1	--
P1L E03-10M	1	3	--	--	1	--	--	--	--
P1L E03-15M	1	3	--	--	--	--	1	--	--
P1L E03-20M	1	3	--	--	--	--	--	--	1
P1L E04-10M	1	4	--	--	1	--	--	--	--
P1L E04-15M	1	4	--	--	--	--	1	--	--
P1L E04-20M	1	4	--	--	--	--	--	--	1
P1L E30-10	1	--	3	1	--	--	--	--	--
P1L E30-15	1	--	3	--	--	1	--	--	--
P1L E30-20	1	--	3	--	--	--	--	1	--
P1L E40-10	1	--	4	1	--	--	--	--	--
P1L E40-15	1	--	4	--	--	1	--	--	--
P1L E40-20	1	--	4	--	--	--	--	1	--
P1L E30-10M	1	--	3	--	1	--	--	--	--
P1L E30-15M	1	--	3	--	--	--	1	--	--
P1L E30-20M	1	--	3	--	--	--	--	--	1
P1L E40-10M	1	--	4	--	1	--	--	--	--
P1L E40-15M	1	--	4	--	--	--	1	--	--
P1L E40-20M	1	--	4	--	--	--	--	--	1

**Tested as full systems. Individual SSS available on VeraSol website.

The SKUs in the table are interpreted as follows. In P1L [XX]-[XXX]:

When the digits in [XX]-[XXXX] are shown, the default components may be changed as follows:

Digit 1: The type of Battery, E: 6.8Ah

Digit 2: The qty of 3 setting bulbs

Digit 3: The qty of 2 setting bulbs

Digit 4-5: The power of solar panel [10W, 15W, 20W]

Digit 6: Signifies if mono-si solar panel, no 6th digit signifies poly-si solar panel

NOTICE:

Only the kits denoted with ** were tested as full systems according to Edition 4 of IEC 62257-9-5 and passed IEC 62257-9-8 standards. An Individual Standardized Specification Sheet (SSS) that reports system-level performance is available for these systems at VeraSol.org. Systems that were not tested, but that were developed using components from the component family will perform differently than the system(s) shown in the individual system-level SSS. All systems listed above are regarded to have passed IEC 62257-9-8.

Unless otherwise noted, the following information applies to all listed systems and components:

Warranty Information

A 2-year warranty covering manufacturing defects in the system.

Available Daily Electrical Energy and Port Information

Beebeejump Technology

P1L Family

System Name	Available Daily Electrical Energy (Wh/day)	Includes ports for charging?
P1L E3-10**	41	yes
P1L E3-15	44	yes
P1L E3-20	45	yes

**Tested as full systems. Individual SSS available on VeraSol website.

NOTICE:

The available daily electrical energy (Wh/day) is calculated for fully tested systems following the energy service calculations as described in IEC/TS 62257-9-5 Ed. 4. For products in a family that are not tested as a full system, estimations of available daily electrical energy (Wh/day) are calculated according to an alternative method using data from the test reports of fully-tested products and components.