VeraSol Standardized Specifications Book

Manufacturer: BeeBeeJump Technology Co., Ltd

Component Family Name: Beebeesolar S1 Plus Family

Date of Standardized

Specifications Book Expiration:

June 30, 2026

Verify Online: https://data.verasol.org/products/sek/bbj-s1pfamily

Contact Information: info@beebeejump.com

Website: https://www.beebeejump.ng



This VeraSol Standardized Specifications Book presents a **component-level Standardized Specifications Sheet** listing the available components in the product family by component type, each individual component's performance rating, and performance results for each component tested according to the Edition 4 of IEC 62257-9-5. Following the component-level Standardized Specifications Sheet is a **list of the systems** covered by this Specifications Book that use combinations of these components.

NOTICE: Systems or kits developed using components from the component family will each perform differently and have not all been evaluated on a system-level basis. All systems listed in this Specifications Book are regarded to have passed IEC TS 62257-9-8.

Quality Standards Framework Version: 2023

Revision: 2025.12

Component-Level Standardized Specifications Sheet

BeeBeeJump Technology Co., Ltd Beebeesolar S1 Plus Family

Battery / Control Box				
Name / Model Number	Battery Chemistry	Nominal Voltage (V)	Battery Capacity Rating (mAh)	Measured Battery Capacity (mAh)
25 Ah main unit battery	Lithium iron phosphate	12.8	25000	25100

PV Module								
Name / Model Number	Peak Power at STC Rating (W)	Measured Peak Power at STC (W)						
mono-si 80 W PV module	80	81						
mono-si 100 W PV module	100	Not tested						
mono-si 120 W PV module	120	Not tested						
mono-si 160 W PV module	160	145						
mono-si 200 W PV module	200	195						

Light Sources*								
	Luminous I	Flux Rating n)	Measured Flux		Measured Lamp Efficacy (lm/W)			
Name / Model Number	High	Medium	High	Medium	High	Medium		
9.5 W LED bulb - 2 Setting	860	-	850		92			
9.5 W LED bulb - 3 Setting	860	1	970	570	100	130		

Appliances*					
Name / Model Number	Description	Rated Power (W)	Measured Power During Use (W)	Rated Battery Capacity (mAh)	Measured Battery Capacity (mAh)
Fan	A standing fan (16" diameter, 13 W power).	Not Stated	13	n/a	n/a

^{*}Light points and appliances may perform differently when used with different systems.

NOTICE: As indicated, not all components listed on this page were tested according to the Quality Test Method (QTM) in Edition 4 of IEC 62257-9-5. However, based on the satisfactory performance of the tested components in the family, the components that were not tested are regarded to have passed IEC TS 62257-9-8:2020. In addition, all tested components passed an internal inspection, the full array of applicable QTM durability tests, as well as ingress protection testing (where applicable).

List of Covered Systems BeeBeeJump Technology Co., Ltd Beebeesolar S1 Plus Family

	Number of e	each compon	ent included	in each syst	tem					
System Name	25 Ah main unit	9.5 W LED bulb - 2 Setting	9.5 W LED bulb - 3 Setting	80 W PV module	100W PV module	120W PV module	160 W PV module	200 W PV module	Fan	-
S1 Plus A20-160 **	1	2	0				1		1	-
S1 Plus A20-1601	1	2	0				1		1	-
S1 Plus A40-160 / Lumos L1	1	4	0				1		-	-
S1 Plus A40-1601	1	4	0				1		1	-
S1 Plus A20-080	1	2	0	1					-	-
S1 Plus A20-0801	1	2	0	1					1	
S1 Plus A22-080	1	2	2	1	-	-	-	-	-	-
S1 Plus A22-0801	1	2	2	1				-	1	
S1 Plus A20-100	1	2	0		1	-	-	-	-	-
S1 Plus A20-1001	1	2	0	-	1	-	-	-	1	-
S1 Plus A22-100	1	2	2		1	-	-	-		-
S1 Plus A22-1001	1	2	2	-	1	-	-	-	1	-
S1 Plus A20-120	1	2	0			1	-	-	ı	ı
S1 Plus A20-1201	1	2	0	-	-	1	-	-	1	1
S1 Plus A22-120	1	2	2			1		-	ı	I
S1 Plus A22-1201	1	2	2			1	-	-	1	ı
S1 Plus A20-200	1	2	0					1	ı	ı
S1 Plus A20-2001	1	2	0					1	1	ı
S1 Plus A40-200	1	4	0					1	1	-
S1 Plus A40-2001	1	4	0					1	1	ı
S1 Plus B20-160	1	2	0				1	-	ı	ı
S1 Plus B20-1601	1	2	0			-	1	-	1	ı
S1 Plus B40-160	1	4	0				1	-	ı	ı
S1 Plus B40-1601	1	4	0			-	1	-	1	ı
S1 Plus B20-080	1	2	0	1					-	-
S1 Plus B20-0801	1	2	0	1					1	
S1 Plus B22-080	1	2	2	1						
S1 Plus B22-0801	1	2	2	1					1	
S1 Plus B20-100	1	2	0		1				-	-
S1 Plus B20-1001	1	2	0		1		-		1	-
S1 Plus B22-100	1	2	2		1				-	-
S1 Plus B22-1001	1	2	2		1	-	-	-	1	-

S1 Plus B20-120	1	2	0			1				
S1 Plus B20-1201	1	2	0			1			1	
S1 Plus B22-120	1	2	2			1				
S1 Plus B22-1201	1	2	2			1			1	
S1 Plus B20-200	1	2	0					1		
S1 Plus B20-2001	1	2	0	-	-	-	-	1	1	-
S1 Plus B40-200	1	4	0					1		
S1 Plus B40-2001	1	4	0	-	-	-	-	1	1	-
S1 Plus A02-160 **	1	0	2		-		1	-		-
S1 Plus A02-1601	1	0	2				1		1	
S1 Plus A03-1601	1	0	3		-	-	1	-	1	-
S1 Plus A04-160 / Lumos L1	1	0	4			-	1	-	-	-
S1 Plus A04-1601	1	0	4	-	-	-	1	-	1	-
S1 Plus A02-080	1	0	2	1	-	-	-	-		-
S1 Plus A02-0801	1	0	2	1	-	-	-	-	1	-
S1 Plus A03-0801	1	0	3	1	-	-	-	-	1	-
S1 Plus A02-100	1	0	2	-	1	-	-	-		-
S1 Plus A02-1001	1	0	2	-	1	-	-	-	1	-
S1 Plus A03-1001	1	0	3		1				1	
S1 Plus A02-120	1	0	2	-	-	1	-	-		
S1 Plus A02-1201	1	0	2		-	1	-	-	1	
S1 Plus A03-1201	1	0	3		-	1	-	-	1	-
S1 Plus A02-200	1	0	2				-	1		-
S1 Plus A02-2001	1	0	2				-	1	1	-
S1 Plus A03-2001	1	0	3					1	1	
S1 Plus A04-200	1	0	4		-	-	-	1		
S1 Plus A04-2001	1	0	4					1	1	

^{**}Tested as full systems. Individual SSS available on VeraSol website.

The SKUs in the table are interpreted as follows.In S1Plus [XXX]-[XXXX]:

When the digits in [XXX]-[XXXX] are shown, the default components may be changed as follows: Digit 1: The type of Battery: Battery A = 27Ah, Battery B = 25Ah. (measured capacity) Digit 2: The qty of 2 setting bulbs
Digit 3: The qty of 3 setting bulbs

Digit 4~6:The power of solar panel : They are 80W,100W,120W,160W,200W

Digit 7: The qty of FAN,0 means none and can be omitted.

NOTICE:

Only the kits denoted with ** were tested as full systems according to Edition 4 of IEC 62257-9-5 and passed IEC 62257-9-8 standards. An Individual Standardized Specification Sheet (SSS) that reports system-level performance is available for these systems at VeraSol.org. Systems that were not tested, but that were developed using components from the component family will perform differently than the system(s) shown in the individual system-level SSS. All systems listed above are regarded to have passed IEC 62257-9-8.

Unless otherwise noted, the following information applies to all listed systems and components:

Warranty Information

A 2-year warranty covering manufacturing defects in the system and a 1-year warranty for accessories

^{***}The Lumos L1 is co-branded by Lumos Global BV and is equivalent to the Beebeejump version. For more details, please visit the product's listing at https://data.verasol.org/products/sek/lumos-l1

Available Daily Elelctrical Energy and Port Information

BeeBeeJump Technology Co., Ltd Beebeesolar S1 Plus Family

System Name	Available Daily Electrical Energy (Wh/day)	Includes ports for charging?
S1 Plus A20-160**	400	yes
S1 Plus A20-1601	400	yes
S1 Plus A40-160 / Lumos L1	400	yes

^{**}Tested as full systems. Individual SSS available on VeraSol website.

NOTICE:

The available daily electrical energy (Wh/day) is calculated for fully tested systems following the energy service calculations as described in IEC/TS 62257-9-5 Ed. 4. For products in a family that are not tested as a full system, estimations of available daily electrical energy (Wh/day) are calculated according to an alternative method using data from the test reports of fully-tested products and components.