

ACOLOR Solar Lighting System

ACOLOR-70

Brand Name: Afreesun Limited

Results based on test procedures detailed in IEC 62257-9-5 v.4

Verify online:

<https://data.verasol.org/products/sek/afs-acolor70>

Valid until: October 31, 2025



Meets the Lighting Global Pico-PV Quality Standards



Mobile charging

PAYG

Pay-As-You-Go option available

4

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system.

PERFORMANCE DETAILS

	Appliance ^a	Description	Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
			Used alone ^b	Used in combination ^c
included in kit	Lantern-10 (Desk Lamp)	1 light point on (Super) totaling 130 lumens and 0.76 W power	6.3 hours	1.5 hours
	Lantern-20	3 light points on (Super) totaling 660 lumens and 3.6 W power	6 hours	5.7 hours
sold separately	Mobile phone	Smart phone (5.7 Wh battery)	1.1 full charge(s)	0.38 full charge(s)
	Radio	1 Ah - 3.7 V battery and power consumption of 0.5 W while in use	13 hours	1.1 hours

Available daily electrical energy^c (Wh/day)

25

Performance measure

Brightness setting: Super

Lighting full battery run time^d for Lantern-20 (hours)

6.0

Lighting full battery run time of the Lantern-10 (Desk Lamp Setting) (hours)

6.3

Total lighting service (lumen-hours/solar-day)
(includes the both main lighting unit and any lights with internal batteries included with the product)

4600

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS


Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^a (lm/W)	CR ^f	CCT ^g	Distribution type	Lumen maintenance ^h
Lantern-10	1	3	Desk Lamp	130	150	68	5000	Wide	100%
		2	Torch	110	110	68	5000	Wide	100%
Lantern-20	3	4	High	200	150	69	5000	Wide	100%

^a Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

PORTS		
4	USB 2.0 type A	 Mobile phones and radios can be charged, adapters are included. One USB port in Lantern-10 and one USB port in each Lantern-20 (3 included in kit).
DURABILITY		
Overall durability and workmanship		Pass
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection. Met IP67
Level of water protection	Main Unit (Lantern-10)	Has protection from occasional rain; met IP67
	10 W PV module	Has protection from permanent outdoor exposure
	Main Unit (Lantern-20)	Has protection from occasional rain; met IP67
SOLAR DETAILS		
PV module type		Polycrystalline silicon
PV maximum power		9.1 watts
MAIN UNIT BATTERY DETAILS		
Battery replaceability		Not easily replaceable with common tools.
Battery chemistry		Lithium-ion
Battery package type		1x18650
Battery capacity Lantern-10 and Lantern-20		2.6 Ah
Battery nominal voltage Lantern-10 and Lantern-20		3.7 V
Battery status indication		Lantern-10 has one indicator for battery state of charge and PV charging. Lantern-20 has two indicators for battery state of charge and PV charging.
PRODUCT DETAILS		
Company name		Afreesun Limited
Brand name		ACOLOR-70
Product name		ACOLOR Solar Lighting System
Product model / ID number		ACOLOR-70
Contact information		sales@afreesun.com
Website		www.afreesun.com
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.
Mass		
SSS INFORMATION		
Specs sheet expiration date		October 31, 2025
Quality standards framework version		2024
Revision		2024.07