

Bright SunBell

SunBell 2.0 Y
Bright Products

Verify online:

<https://data.verasol.org/products/sek/bp-sb2y>

Valid until: November 30, 2023

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the requirements in IEC TS 62257-9-8:2020 for Size A Kits



Mobile charging

1

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects.

PERFORMANCE DETAILS

VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
				Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	1 light point on high totaling 110 lumens and 0.8 W power	6 hours	1.7 hours
no	not included	Smart Phone	Smart phone (5.7 Wh battery)	0.6 full charge(s)	0.4 full charge(s)

Available daily electrical energy ^e (Wh/day)	4.1
---	-----

Performance measure	Brightness setting: High
Lighting full battery run time ^d for main unit (hours)	6.3
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	480

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS


Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
Integrated light	1	3	High	110	140	84	4100	Wide	100%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES		
Product Housing	★ UV resistant plastic	
Ingress protection	★ Product meets IP64 (Has protections from dust and frequent rain)	
PORTS		
1	USB 2.0 type A  Mobile phones can be charged. Adapters are included.	
DURABILITY		
Overall durability and workmanship	Pass	
Durability tests passed	Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests	
Level of water protection	Main Unit	Has protection from frequent rain; met IPX3
	PV module	Has protection from permanent outdoor exposure
SOLAR DETAILS		
PV module type	Monocrystalline silicon	
PV maximum power	1.7 watts	
MAIN UNIT BATTERY DETAILS		
Battery replaceability	Not easily replaceable with common tools.	
Battery chemistry	Lithium iron phosphate	
Battery package type	18650	
Battery capacity	1.5 Ah	
Battery nominal voltage	3.2 V	
Battery status/ other indicator lights	The indicator shows charging and discharging conditions.	
PRODUCT DETAILS		
Manufacturer name	Bright Products	
Product name	Bright SunBell	
Product model / ID number	SunBell 2.0 Y	
Contact information	info@bright-products.com	
Website	http://bright-products.com/	
Dimensions (entire product in package)	15 x 15 x 16 cm	
Mass	693 g	
SSS INFORMATION		
Specs sheet expiration date	November 30, 2023	
Revision	2022.10	