/alid until: March 31 2023

Results based on test procedures detailed in IEC TS 62257-9-5



Meets the Lighting Global Solar Home System Kit Quality Standards



Mobile charging

Payg

Pay-As-You-Go option available

6

Light point(s)



Plug-and-play



Run time after a typical day of solar

WARRANTY INFORMATION

PERFORMANCE DETAILS

The product provides a 2-year warranty that covers manufacturing defects that prevent operation under normal use and protection from early component failure

				charging		
				(assuming 5kWh/m²/day)		
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c	
yes	included	Main lighting unit	6 light points on high mode totaling 820 lumens and 5.4 W power	24 hours	10 hours	
yes	included	Television	32" diagonal (15 W power consumption while in-use)	11 hours	5.4 hours	
no	not included	Mobile phone	Basic phone (3.7 Wh battery)	25 full charge(s)	2.7 full charge(s)	

Available daily electrical energy ^c (Wh/day)	150
Available daily electrical energy (Wh/day)	150

Performance measure	Brightness setting: High Mode		
Lighting full battery run time ^d for main unit (hours)	24		
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	19800		

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCTa	Distribution type	Lumen maintenance ^h
Hanging Lamp	6	3	High Mode	140	160	83	5200	Wide	99%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

¹Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEAT	URES						
PAYG	*	Pay-As-You-Go enabled					
PORTS 2	USB 2.0 type A		Mobile phones can be charged. Adapters are included.				
3 DURABILITY	Barrel jack		12 V ports available to charge devices and power appliances and light points.				
	h, and workmanahin		Pass				
Overall durability and workmanship			Pass				
Durability tests passed			Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests				
		Main Unit with integrated TV	Water ingress protection not tested, meant for indoor use only.				
Level of water protection		PV module	Has protection from permanent outdoor exposure.				
		Main Lighting Unit	Water ingress protection not tested, meant for indoor use only.				
SOLAR DETAIL							
PV module type			Monocrystalline silicon				
PV maximum po	ower		40 watts				
	TTERY DETAILS						
Battery replaces	ability		Easily replaceable with common tools; however, the warranty is void if product is opened.				
Battery chemistr	ry		Lithium iron phosphate				
Battery package	e type		26650				
Battery capacity			10 Ah				
Battery nominal	voltage		12.8 V				
Battery status in	dication		One red power indicator shows the TV working status.				
PRODUCT DET	AILS						
Manufacturer na	ame		Cello				
Product name			Cello Solar TV 32"				
Contact informa	tion		klaus@celloelectronics.com				
Website			www.celloelectronics.com				
Tested as			OOLU Solar TV 32"				
Dimensions (entire product in package)			86 x 53 x 26 cm				
Mass	-		13400 g				
SSS INFORMAT	ION						
Specs sheet expiration date			March 31 2023				
Quality standards framework version			2021				
Revision			2021.03				