A2 Solar Lantern



Meets the Lighting Global Pico-PV Quality Standards



Light point(s)

Plug-and-play



Verify online: https://data.verasol.org/products/sek/dl-A2 Valid until: November 30, 2022

WARRANTY INFORMATION

A 1-year warranty covering manufacturing defects. PERFORMANCE DETAILS

| Setting | Description | Run time after a typical day of solar charging (assuming 5kWh/m ² /day) | Total light output (lumens) |
|---------|--------------------------|---|--------------------------------|
| On | One LED on, 0.22 W power | 4 hours | 27 lumens |

Available daily electrical energy (Wh/day)

| Performance measure | Brightness setting: On | | |
|---|------------------------|--|--|
| Lighting full battery run time (hours) | 5.3 | | |
| Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product) | 110 | | |

1.2

| LIGHTING DETAILS | ILS | | | | | | | | |
|------------------|--------------------|--------------------|---------|----------------------|---------------------------|-------|--------|-------------------|--------------------------|
| Lamp name | Number of lamps | Number of settings | Setting | Light output (Im) | Lumen efficacy* (Im/W) | CRI** | CCT*** | Distribution type | Lumen maintenance**** |
| LED | 1 | 1 | On | 27 | 140 | 81 | 5500 | Wide | 99% |

* Lumen efficacy is the power consumption at a light point during the light output test.
** Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.
*** Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)
*** Percent of the original light output that remains after 2,000 hours of run time

| SPECIAL FEATURES | | | | | | |
|--|--|---|--|--|--|--|
| Product Housing 🔶 VV Resistant Plastic | | | | | | |
| DURABILITY | | | | | | |
| Overall durability and workmanship | | Pass | | | | |
| Durability tests passed | | Switch test, Drop test, Physical ingress protection | | | | |
| Level of water protection | Main Unit with Integrated PV Module | Has protection from frequent rain; met with IPX1 and an appropriate warning label | | | | |
| SOLAR DETAILS | | | | | | |
| PV module type | | Monocrystalline silicon | | | | |
| PV maximum power | | 0.3 watts | | | | |
| MAIN UNIT BATTERY DETAILS | | | | | | |
| Battery replaceability | | Not easily replaceable with common tools. | | | | |
| Battery chemistry | | Lithium iron phosphate | | | | |
| Specific Li-ion battery chemistry | | lithium iron phosphate | | | | |
| Battery package type | | IFR 14430 | | | | |
| Battery capacity | | 0.3 Ah | | | | |
| Battery nominal voltage | | 3.2 V | | | | |
| Battery status/ other indicator lights | | one indicator for charging | | | | |
| PRODUCT DETAILS | | | | | | |
| Manufacturer name | | d.light design | | | | |
| Product name | | A2 Solar Lantern | | | | |
| Product model / ID number | | A2 | | | | |
| Contact information | | testing@dlight.com | | | | |
| Website | | www.dlight.com | | | | |
| Dimensions (entire product in package) | | 7.2 x 7.2 x 3.5 cm | | | | |
| Mass | | 90 g | | | | |
| SSS INFORMATION | | | | | | |
| Specs sheet expiration date | | November 30, 2022 | | | | |
| Revision | | 2022.05 | | | | |