

Solar Lantern

T200

Brand name: d.light

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8

Verify online:

<https://data.verasol.org/products/sek/dl-t200>

Valid until: March 31, 2027



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging

1

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system

PERFORMANCE DETAILS

VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
				Used alone ^b	Used in combination ^c
yes	included	Main lighting unit - torch	1 light point on high totaling 210 lumens and 1.9 W power	4.4 hours	2 hours
yes	included	Main lighting unit - tubelight	1 light point on high totaling 130 lumens and 1.9 W power	4.4 hours	--
no	not included	Smart phone	Smart phone (5.7 Wh battery)	0.92 full charge(s)	0.5 full charge(s)

Available daily electrical energy ^c (Wh/day)	7.1
---	-----

Performance measure	Brightness setting: One light on "high" (torch)
Lighting full battery run time ^d for main unit (hours)	4.6
Total lighting service (lumen-hours / solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	920

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS

Lamp name	Number of lamps	Number of settings	Setting name	Light output (lm)	Power consumption (W)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
Solar Lantern T200	1	4	high (torch)	210	1.9	110	74	5700	Narrow	100%
			high (tubelight)	130	1.9	70	84	6600	Wide	100%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K).

^h Percent of the original light output that remains after 2,000 hours of run time.

PORTS		
1	USB 2.0 type A  Mobile phones and radios can be charged. Adapters are included.	
DURABILITY		
Overall durability and workmanship	Pass	
Durability tests passed	Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests	
Level of water protection	Main Lighting Unit	Has protection from occasional rain; met with appropriate warning label
	PV module	Has protection from permanent outdoor exposure
SOLAR DETAILS		
PV module type	Polycrystalline silicon	
PV maximum power	2.5 W	
PV rated power	2.8 W	
PV open-circuit voltage (V _{oc})	6.36 V	
MAIN UNIT BATTERY DETAILS		
Battery replaceability	Easily replaceable with common tools; however, the warranty is void if product is opened.	
Battery chemistry	Lithium-ion	
Specific Li-ion battery chemistry	lithium cobalt oxide	
Battery package type	18650	
Battery capacity	2.4 Ah	
Rated Battery capacity	2.4 Ah	
Battery nominal voltage	3.7 V	
Battery status / other indicator lights	One indicator for PV charging	
PRODUCT DETAILS		
Company name	d.light design Ltd.	
Brand Name	d.light	
Product name	Solar Lantern	
Product model / ID number	T200	
Contact information	testing@dlight.com	
Website	www.dlight.com	
Dimensions (entire product in package)	Multiple packages. Contact manufacturer for more information.	
Mass	n/a	
SSS INFORMATION		
Specs sheet expiration date	March 31, 2027	
Revision	2025.03	