Verify online: https://data.verasol.org/products/sek/dl-t500r

ults based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging



Pay-As-You-Go option available



Light point(s)



Plug-and-play



Run time after a typical day of solar

## WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system

## ERFORMANCE DETAILS

				(assuming 5kWh/m²/day)		
VeraSol Certified?	Included in Kit?	Appliance <sup>a</sup>	Description	Used alone <sup>b</sup>	Used in combination <sup>c</sup>	
yes	included	Main lighting unit (Integrated Torch)	Integrated torch with a power consumption of 1.8 W while in-use	9.7 hours	4.2 hours	
yes	included	Integrated Side Lamp	Integrated lamp with a power consumption of 1.8 W while in-use	9.7 hours	3.1 hours	
yes	included	Integrated Radio	integrated battery with a power consumption of 0.29 W while in-use	66 hours	1 hours	
no	not included	Mobile phone	Basic phone (3.7 Wh battery)	2 full charge(s)	1 full charge(s)	

-	
Available daily electrical energy <sup>c</sup> (Wh/day)	15

Performance measure	Brightness setting: high		
Lighting full battery run time <sup>d</sup> for main unit (hours)	9.9		
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	1920		

<sup>&</sup>lt;sup>a</sup> Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy <sup>e</sup> (lm/W)	CRI <sup>f</sup>	CCT <sup>g</sup>	Distribution type	Lumen maintenance <sup>h</sup>
Main Unit (Integrated Torch)	1	3	high	200	110	72	5400	Narrow	100%
Integrated Side Lamp	1	2	high	120	66	85	6700	Wide	99%

<sup>&</sup>lt;sup>e</sup> Lumen efficacy is the power consumption at a light point during the light output test.

<sup>&</sup>lt;sup>b</sup> Without any other loads used during the run time

<sup>&</sup>lt;sup>c</sup> Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

<sup>&</sup>lt;sup>f</sup>Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

<sup>&</sup>lt;sup>9</sup> Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

<sup>&</sup>lt;sup>h</sup> Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES							
Multi-use		The solar lantern can b	n can be used as torch, ambient light or radio.				
PORTS							
1 4	JSB 2.0 type A		Mobile phones can be charged. Adapters are included.				
DURABILITY							
Overall durability and workmanship			Pass				
Durability tests passed			Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests				
Level of water protection		Main Unit	Has protection from occasional rain; met with appropriate warning label				
		PV module	Has protection from permanent outdoor exposure.				
SOLAR DETAILS							
PV module type			Polycrystalline silicon				
PV maximum power			5.6 watts				
MAIN UNIT BATTERY	/ DETAILS						
Battery replaceability			Easily replaceable with common tools; however, the warranty is void if product is opened.				
Battery chemistry			Lithium-ion				
Specific Li-ion battery	chemistry		lithium cobalt oxide				
Battery package type			2x 18650				
Battery capacity			4.8 Ah				
Battery nominal voltag	е		3.7 V				
Battery status/ other in	ndicator lights		1 LED on the screen on the side shows battery status				
PRODUCT DETAILS							
Manufacturer name			d.light design inc.				
Product name			Solar Lantern				
Product model / ID number			T500R				
Contact information			testing@dlight.com				
Website			www.dlight.com				
Dimensions (entire product in package)			28 x 18 x 19 cm				
Mass			1520 g				
SSS INFORMATION							
Specs sheet expiration	n date		January 31, 2026				
Revision			2024.04				