

Fenix Power 2

F0113BJ
Engie Mobisol GmbH

Verify online:
<https://data.verasol.org/products/sek/emb-fp2>
Valid until: March 31, 2023

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the requirements in IEC TS 62257-9-8:2020 for Size A Kits



Mobile charging

PAYG

Pay-As-You-Go option available

2

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 3-year warranty for the system and PV module and a 2-year warranty for lights, appliances, and accessories

PERFORMANCE DETAILS

VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
				Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	2 light points on High totaling 380 lumens and 3.5 W power	8.9 hours	5.2 hours
no	not included	Mobile phone	Smart phone (5.7 Wh battery)	3 full charge(s)	1.3 full charge(s)

Available daily electrical energy ^c (Wh/day)	22
---------------------------------------------------------	----

Performance measure	Brightness setting: High
Lighting full battery run time ^d for main unit (hours)	9.4
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	3380

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS



Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
LED Lamp	2	3	High	190	110	84	5100	Wide	100%
			Medium	99	120	83	5100	Wide	--

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

PORTS		
1	USB 2.0 type A	 Mobile phones can be charged; adapters included
2	Barrel jack	 Two 12 V ports are available to power appliances or light points
DURABILITY		
Overall durability and workmanship		Pass
Durability tests passed		Switch test, Strain relief test, Physical ingress protection, PV durability tests
Level of water protection	Main Unit	Water ingress protection not tested, meant for indoor use only.
	PV module	Has protection from permanent outdoor exposure
	LED Lamp	Water ingress protection not tested, meant for indoor use only.
SOLAR DETAILS		
PV module type		Polycrystalline silicon
PV maximum power		10 watts
MAIN UNIT BATTERY DETAILS		
Battery replaceability		Not easily replaceable with common tools.
Battery chemistry		Lithium-ion
Specific Li-ion battery chemistry		lithium nickel manganese cobalt oxide
Battery package type		2x18650
Battery capacity		7.9 Ah
Battery nominal voltage		3.6 V
Battery status indication		One for lock status, one for link status, five for battery state of charge, three for PV charging rate, and one for hazard status.
PRODUCT DETAILS		
Manufacturer name		Engie Mobisol GmbH
Product name		Fenix Power 2
Product model / ID number		F0113BJ
Contact information		china_opm.a2e@engie.com
Website		https://www.fenixintl.com/
Dimensions (entire product in package)		39 x 27 x 11 cm
Mass		2820 g
SSS INFORMATION		
Specs sheet expiration date		March 31, 2023
Revision		2021.11