## Sun King Home 400 easybuy SK503/SK505 Greenlight Planet

sults based on test procedures detailed in IEC TS 62257-9-5

https://data.verasol.org/products/sek/glp-home400



**PAYG** 

Meets the Lighting Global Solar Home System Kit Quality Standards



Pay-As-You-Go option available

5

Light point(s)

Plug-and-play



Run time after a typical day of solar charging

A 2-year warranty covering manufacturing defects in the system and the battery.

				(assuming 5kWh/m²/day)		
VeraSol Certified?	Included in Kit?	Appliance <sup>a</sup>	Description	Used alone <sup>b</sup>	Used in combination <sup>c</sup>	
yes	included	Main lighting unit	5 light points on (High) totaling 1200 lumens	10 hours	6.8 hours	
yee	Television		19" diagonal	11 hours	3.4 hours	
no	not included	Mobile Phone	Basic Phone (3.7 Wh battery)	18 full charge(s)	1.7 full charge(s)	

Available daily electrical energy (Wh/day)	88
Available daliy electrical energy (vvn/day)	00

Performance measure	Brightness setting: High		
Lighting full battery run time <sup>d</sup> for main unit (hours)	10		
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	8400		

<sup>&</sup>lt;sup>a</sup> Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy <sup>e</sup> (lm/W)	CRI <sup>f</sup>	ССТ <sup>9</sup>	Distribution type	Lumen maintenance <sup>h</sup>
200 lm Lamp	2	3	High	200	130	70	4900	Wide	94%
Tubelight	2	3	High	370	160	72	6215	Wide	100%
Motion Sensor Lamp	1	1	On	95	130	71	4931	Wide	100%

<sup>&</sup>lt;sup>e</sup> Lumen efficacy is the power consumption at a light point during the light output test.

<sup>&</sup>lt;sup>b</sup> Without any other loads used during the run time

<sup>&</sup>lt;sup>c</sup> Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

<sup>&</sup>lt;sup>f</sup> Color Rendering Index. An index of 100 is equivalent to vieiwing objects in daylight; above 80 is considered good.

<sup>&</sup>lt;sup>9</sup> Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

<sup>&</sup>lt;sup>h</sup> Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES  SK5		SK503 has keypad PAY0	SK503 has keypad PAYG system				
PAYG Payment Systems		SK505 has GSM PAYG system					
PORTS 2	USB 2.0 type A		Mobile phones and radios can be charged. Adapters are included.				
4			Four 12 V ports available to charge devices and power appliances and light points.				
•	Barrel jack		Four 12 v ports available to charge devices and power appliances and light points.				
DURABILITY Overall durability and workmanship			Pass				
Durability tests pas	ssed		Switch test, Strain relief test, Physical ingress protection				
		Main Unit	Water ingress protection not tested, meant for indoor use only.				
Level of water prot	tection	PV module	Has protection from permanent outdoor exposure				
•		Television	Water ingress protection not tested, meant for indoor use only.				
SOLAR DETAILS							
PV module type			Polycrystalline silicon				
PV maximum powe	er		38 watts				
MAIN UNIT BATT	ERY DETAILS						
Battery replaceabil	lity		Easily replaceable with common tools.				
Battery chemistry			Lithium-ion				
Battery package ty	/ре		3s5p 18650				
Battery capacity			12.5 Ah				
Battery nominal vo	oltage		11.1 V				
Battery status indi			5 LEDs indicate the status of the battery and 5 LEDs indicate the charging rate.				
MARKS AND CER	RTIFICATIONS						
Factory certificatio			ISO 9001; ISO 14001:2004				
PRODUCT DETAI	ILS						
Manufacturer nam	е		Greenlight Planet				
Product name			Sun King Home 400 easybuy				
Product model / ID number			SK503/SK505				
Contact information			sales@greenlightplanet.com				
Website			www.greenlightplanet.com				
Dimensions (entire product in package)			Multiple packages. Contact manufacturer for more information.				
Mass			8230 g				
S INFORMATION							
Specs sheet expiration date			June 30, 2022				
Quality standards framework version			2018				

2021.05

Revision