Sun King Home 40 Plus SK-417 / SK-419 Greenlight Planet

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the requirements in IEC TS 62257-9-8:2020 for Size A Kits



Mobile charging



Light point(s) Plug-and-play



Run time after a typical day of solar charging

WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects.

PERFORMANCE DETAILS

| | | (assuming 5kWh/m²/day) | | | |
|--------------------|---------------------|------------------------|--|-------------------------|----------------------------------|
| VeraSol Certified? | Included in Kit? | Appliance ^a | Description | Used alone ^b | Used in combination ^c |
| yes | not included | Main lighting unit | 2 light points on (Turbo mode) totaling 390 lumens and 2.6 W power | 7.2 hours | 4.9 hours |
| no | not included | Mobile phone | Basic phone (3.7 Wh battery) | 3.6 full charge(s) | 1.2 full charge(s) |

Available daily electrical energy^c (Wh/day) 17

| Performance measure | Brightness setting: Turbo mode | |
|---|--------------------------------|--|
| Lighting full battery run time ^d for main unit (hours) | 7.2 | |
| Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal hatteries included with the product) | 2880 | |

- Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.
- ^b Without any other loads used during the run time
- ^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.
- d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS

| Lamp name | Number of lamps | Number of settings | Setting | Light output (lm) | Lumen efficacy ^e (Im/W) | CRI ^f | CCTg | Distribution type | Lumen maintenance ^h |
|---------------|--------------------|--------------------|---------------|-------------------|---------------------------------------|------------------|------|-------------------|--------------------------------|
| LED tubelight | 2 | 3 | Turbo mode | 200 | 160 | 82 | 6100 | Wide | 100% |

^e Lumen efficacy is the power consumption at a light point during the light output test.

^fColor Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

| SPECIAL FEATUR | ES | | | | | |
|--|-----------------|---|--|--|--|--|
| PAYG | * | | 40 Plus Easy Buy (SK-419) is Pay-As-You-Go enabled. 40 Plus (SK-417) is the non-PAYG version. | | | |
| PORTS | | Ţ, | | | | |
| 1 | USB 2.0 type A | | Mobile phones can be charged. Adapters are not included. | | | |
| 2 | 2 Barrel jack — | | 5 V ports available to power appliances and light points. | | | |
| DURABILITY | | | | | | |
| Overall durability ar | nd workmanship | | Pass | | | |
| Durability tests passed | | | Switch test, Strain relief test, Physical ingress protection, PV durability tests | | | |
| | | Main Unit | Water ingress protection not tested, meant for indoor use only. | | | |
| Level of water protection | | PV module Has protection from permanent outdoor exposure. | | | | |
| | | Tube light | Water ingress protection not tested, meant for indoor use only. | | | |
| SOLAR DETAILS | | | | | | |
| PV module type | | | Polycrystalline silicon | | | |
| PV maximum powe | Г | | 5.4 watts | | | |
| MAIN UNIT BATTE | RY DETAILS | | | | | |
| Battery replaceabili | ty | | Easily replaceable with common tools. | | | |
| Battery chemistry | | | Lithium-ion | | | |
| Specific Li-ion batte | ery chemistry | | lithium nickel manganese cobalt oxide | | | |
| Battery package typ | ре | | 18650 | | | |
| Battery capacity | | | 2.6 Ah | | | |
| Battery nominal voltage | | | 7.4 V | | | |
| Battery status indication | | | Four digital LED meter to display the remaining battery power | | | |
| PRODUCT DETAIL | S | | | | | |
| Manufacturer name | | | Greenlight Planet | | | |
| Product name | | | Sun King Home 40 Plus | | | |
| Product model / ID number | | | SK-417 / SK-419 | | | |
| Contact information | | | sales@greenlightplanet.com | | | |
| Website | | | www.greenlightplanet.com | | | |
| Dimensions (entire product in package) | | | 57 x 11 x 7 cm | | | |
| Mass | | | 1590 g | | | |
| SSS INFORMATION | | | | | | |
| Specs sheet expirat | | | October 31, 2023 | | | |
| Revision | | | 2021.10 | | | |