Sun King Home 60 Easybuy SK405 Greenlight Planet

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8

Verify online: https://data.verasol.org/products/sek/glp-skhome Valid until: June 30. 2025

Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits Mobile charging PAYG Pay-As-You-Go option available 3 Light point(s) Plug-and-play



WARRANTY INFORMATION A 2-year warranty covering manufacturing defects in the system.

PERFORMANCE DETAILS					
		Run time after a typical day of solar charging (assuming 5kWh/m ² /day)			
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	3 light points on Turbo totaling 300 lumens and 0.5 W of power	5.2 hours	4 hours
no	not included	Mobile phone	Basic phone (3.7 Wh battery)	3 full charge(s)	1 full charge(s)

Available daily electrical energy^c (Wh/day) 14

Performance measure	Brightness setting: Turbo
Lighting full battery run time ^d for main unit (hours)	5.2
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	1610

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (Im)	Lumen efficacy ^e (Im/W)	CRI ^f	CCTª	Distribution type	Lumen maintenance ^h
100 lm lamp	3	3	Turbo	100	110	65	4230	Wide	100%
			Normal	58	140				- not tested -
			Low						- not tested -

^e Lumen efficacy is the power consumption at a light point during the light output test.

^fColor Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES						
PAYG 🔶	Pay-As-You-Go enabled					
PORTS						
2 USB 2.0 type A		Mobile phones and radios can be charged. Adapters are included.				
2 Barrel jack		Two 12 V barrel jacks available to power light points only.				
DURABILITY						
Overall durability and workmanship		Pass				
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection				
	Main Unit	Has protection from occasional rain; met IPX1				
Level of water protection	PV module	Has protection from permanent outdoor exposure				
SOLAR DETAILS						
PV module type		Polycrystalline silicon				
PV maximum power		6.1 watts				
MAIN UNIT BATTERY DETAILS						
Battery replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.				
Battery chemistry		Lithium iron phosphate				
Specific Li-ion battery chemistry		lithium iron phosphate				
Battery package type		4x18650				
Battery capacity		5.9 Ah				
Battery nominal voltage		3.3 V				
Battery status/ other indicator lights		Five digital LED meter to display the remaining battery power and five digital LED meter to display charge effectiveness on a scale of 1 to 5 to help optimize solar module placement.				
PRODUCT DETAILS						
Manufacturer name		Greenlight Planet				
Product name		Sun King Home 60 Easybuy				
Product model / ID number		SK405				
Contact information		nicky@sunking.com				
Website		https://sunking.com/				
Dimensions (entire product in package)		31 x 16 x 19 cm				
Mass		2440 g				
SS INFORMATION						
Specs sheet expiration date		June 30, 2025				
Revision		2023.09				