5

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-

https://data.verasol.org/products/sek/jua-h4g150

Run time after a typical day of solar



WARRANTY INFORMATION

PERFORMANCE DETAILS

A 24-month warranty covering manufacturing defects in the system.

		charging (assuming 5 kWh/m²/day)			
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	5 light points on high totaling 1630 lumens and 16 W power	9.8 hours	4.5 hours
yes	included	Television	24" diagonal (11 W power consumption while in use)	18 hours	2.5 hours
yes	included	Fan	16" standing fan (12 W power consumption while in use)	17 hours	6.2 hours
no	not included	Radio	portable radio (Li-ion battery: 1 Ah, 3.7 V) with rated power consumption of 0.5 W	200 hours	3.7 hours
no	not included	Mobile phone	Smartphone (5.7 Wh battery)	20 full charge(s)	1.4 full charge(s)

Available daily electrical energy ^c (Wh/day) 170	
---	--

Performance measure	Brightness setting: high
Lighting full battery run time ^d for main unit (hours)	9.8
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	16000

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
200 lm lamp	4	2	high	280	130	87	6500	Wide	100%
500 lm lamp	1	2	high	530	100	78	10000	Wide	99%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

⁹ Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEAT	TURES		
PAYG	*	Pay-As-You-Go enabled	
PORTS			
2	USB 2.0 type A		Mobile phones and radios can be charged. Adapters not included.
6	Barrel jack	-	Six 12 V ports available to power light points and appliances.

DURABILITY						
Overall durability and workmanship Durability tests passed		Pass Switch test, Strain relief test, Physical ingress protection, PV durability tests				
						Main Unit
Level of water protection	PV module	Has protection from permanent outdoor exposure				
	200 lm lamp	Water ingress protection not tested, meant for indoor use only.				
	500 lm lamp	Water ingress protection not tested, meant for indoor use only.				
	Television	Water ingress protection not tested, meant for indoor use only.				
SOLAR DETAILS						
PV module type		Polycrystalline silicon				
PV maximum power		58 watts				
MAIN UNIT BATTERY DETAILS						
Battery replaceability		Not easily replaceable with common tools.				
Battery chemistry		Lithium iron phosphate				
Specific Li-ion battery chemistry		lithium iron phosphate				
Battery package type		32700				
Battery capacity		11.7 Ah				
Battery nominal voltage		12.8 V				
Battery status/ other indicator lights		Four indicators for battery state of charge, one indicator for PV charging, three indicators for P credit status				
PRODUCT DETAILS						
Manufacturer name		JUA Energy Co., Ltd.				
Product name		Home Mate H4G-150				
Product model / ID number		H4G-150				
Contact information		hill.ren@juaenergy.com				
Website		www.juaenergy.com				
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.				
Mass		n/a				
SS INFORMATION						
Specs sheet expiration date		September 30, 2024				
Revision		2022.11				