## **Solar Home System**

LM-LFP100

Shenzhen LEMI Technology Development Co. Ltd.

Verify online:

https://data.verasol.org/products/sek/lemi-lfp100

Valid until: September 30, 2025

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the requirements in IEC TS 62257-9-8 for Size B Kits



Mobile charging



Light point(s)



Plug-and-play



## WARRANTY INFORMATION

A 3-year warranty covering manufacturing defects in the system and a 1-year warranty for optional appliances and accessories.

## PERFORMANCE DETAILS

Run time after a typical day of solar charging	
(assuming 5kWh/m²/day)	

VeraSol Certified?	Included in Kit?	Appliance <sup>a</sup>	Description	Used alone <sup>b</sup>	Used in combination <sup>c</sup>
yes	included	Main lighting unit	4 light points (5 W lamps) on "On" totaling 2080 lumens and 18 W power	20 hours	8.2 hours
yes	not included	Torch	56 lumens torch, (Li-ion battery: 1.9 Ah, 3.7 V)	260 hours	8.2 hours
yes	not included	32" television	20 W power consumption while in use	27 hours	4.1 hours
yes	not included	Radio	Portable radio (Li-ion battery: 1 Ah, 3.7 V) with power consumption of 0.5 W while in use	110 hours	6.1 hours
yes	not included	16" pedestal fan	16" pedestal fan (14 W power)	31 hours	10 hours
no	not included	Mobile phone	Basic phone (3.7 Wh battery)	55 full charge(s)	2 full charge(s)

i Available daliv electrical energy (vyri/dav)	Available daily electrical energy <sup>c</sup> (Wh/day)	350
--	---	-----

Performance measure	Brightness setting: Four 5 W lamps on "On"
Lighting full battery run time <sup>d</sup> for main unit (hours)	24
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	41600

<sup>&</sup>lt;sup>a</sup> Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy <sup>e</sup> (Im/W)	CRI <sup>f</sup>	CCT <sup>g</sup>	Distribution type	Lumen maintenance <sup>h</sup>
5 W lamp	4	1	On	520	120	84	6500	Wide	100%

<sup>&</sup>lt;sup>e</sup> Lumen efficacy is the power consumption at a light point during the light output test.

<sup>&</sup>lt;sup>b</sup> Without any other loads used during the run time

<sup>&</sup>lt;sup>c</sup> Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

<sup>&</sup>lt;sup>f</sup>Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

<sup>&</sup>lt;sup>g</sup> Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

<sup>&</sup>lt;sup>h</sup> Percent of the original light output that remains after 2,000 hours of run time

PORTS							
2 USB 2.	0 type A	-	Mobile phones can be charged.				
8 Barrel jack			Five 12 V ports available to power lamps and three 12 V ports available to power TV, far and other appliances.				
1 Cigarette lighter			One 12 V port to power car appliances and other appliances.				
DURABILITY							
Overall durability and workmanship			Pass				
Durability tests passed			Switch test, Strain relief test, Physical ingress protection, PV durability tests				
Level of water protection  Main Unit  PV module		Main Unit	Water ingress protection not tested, meant for indoor use only.				
		PV module	Has protection from permanent outdoor exposure				
SOLAR DETAILS							
PV module type			Polycrystalline silicon				
PV maximum power			98 watts				
MAIN UNIT BATTERY DETA	AILS						
Battery replaceability			Easily replaceable with common tools; however, the warranty is void if product is opened.				
Battery chemistry			Lithium iron phosphate				
Battery package type			32700				
Battery capacity			35 Ah				
Battery nominal voltage			12.8 V				
Battery status/ other indicator lights			One indicator for solar charging, three indicators for battery level, and one indicator for load status.				
PRODUCT DETAILS							
Manufacturer name			Shenzhen LEMI Technology Development Co. Ltd.				
Product name			Solar Home System				
Product model / ID number			LM-LFP100				
Contact information			21988186@qq.com				
Website			http://www.lemi.com.cn/				
Dimensions (entire product in package)			Multiple packages. Contact manufacturer for more information.				
Mass			Multiple packages. Contact manufacturer for more information.				
SSS INFORMATION		-					
Specs sheet expiration date			September 30, 2025				
Revision			2025.04				