Mysol 10W 2 C Solar Home System 10W 2C (M0006 Power system/A0032 Panel) Engie Mobisol GmbH

sults based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8

Valid until: October 31, 2025



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging



Pay-As-You-Go option available



Light point(s)



Plug-and-play



Run time after a typical day of solar

WARRANTY INFORMATION

ERFORMANCE DETAILS

A 3-year warranty for the system and PV module and a 2-year warranty for lights, appliances, and accessories

					rging kWh/m²/day)
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	2 light points on High totaling 380 lumens and 3.5 W power	7.3 hours	3.1 hours
yes	included	Torch	130 lm torch (Li-ion battery: 2.6 Ah, 3.6 V)	12 hours	3.1 hours
no	not included	Mobile phone	Smart phone (5.7 Wh battery)	2.5 full charge(s)	0.8 full charge(s)

Available daily electrical energy ^c (Wh/day)	17

Performance measure	Brightness setting: High
Lighting full battery run time ^d for main unit (hours)	7.4
Lighting full battery run time of the Torch powered by Torch battery (hours)	5.7
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	2500

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
LED Lamp	1	3	High	190	110	84	5100	Wide	100%
LED Lamp	1	3	Medium	99	120	83	5100	Wide	%
Torch	1	2	brighter	130	110	84	5200	Wide	%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES						
PAYG	*	Pay-As-You-Go enabled				
PORTS						
1	USB 2.0 type A		Mobile phones can be charged. Adapters are included.			
2	Barrel jack	-	Ex: 12 V ports available to charge devices and power appliances or light points.			

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

⁹ Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

DURABILITY				
Overall durability and workmanship		Pass		
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests		
	Main Unit	Water ingress protection not tested, meant for indoor use only.		
Level of water protection	PV module	Has protection from permanent outdoor exposure Water ingress protection not tested, meant for indoor use only.		
	LED Light			
	Torch	Has protection from occasional rain; met IPX1		
SOLAR DETAILS				
PV module type		Polycrystalline silicon		
PV maximum power		10 watts		
MAIN UNIT BATTERY DETAILS				
Battery replaceability		Not easily replaceable with common tools.		
Battery chemistry		Lithium-ion		
Specific Li-ion battery chemistry		lithium nickel manganese cobalt oxide		
Battery package type		2x18650		
Battery capacity		7.9 Ah		
Battery nominal voltage		3.6 V		
Battery status/ other indicator lights		One for lock status, one for link status, five for battery state of charge, three for PV charging and one for hazard status.		
PRODUCT DETAILS		<u> </u>		
Manufacturer name		Engie Mobisol GmbH		
Product name		Mysol 10W 2 C Solar Home System		
Product model / ID number		10W 2C (M0006 Power system/A0032 Panel)		
Contact information		china_opm.a2e@engie.com		
Website		https://engie-energyaccess.com		
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.		
Mass		n/a		
SS INFORMATION				
Specs sheet expiration date		October 31, 2025		
Revision		2023.11		