

L220 Task Light & Phone Charger

L220

Brand name: Omnivoltaic

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8

Verify online:

<https://data.verasol.org/products/sek/omni-l220>

Valid until: November 30, 2026



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging

PAYG

Pay-As-You-Go option available

1

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system.

PERFORMANCE DETAILS

				Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	1 light point on Super totaling 210 lumens and 1.1 W power	7.2 hours	3 hours
no	not included	Smart phone	Smart phone (5.7 Wh battery)	1.1 full charge(s)	0.74 full charge(s)
no	not included	Mobile phone	Smart phone (3.7 Wh battery)	1.8 full charge(s)	--

Available daily electrical energy ^c (Wh/day)	8.0
---	-----

Performance measure	Brightness setting: One light on Super
Lighting full battery run time ^d for main unit (hours)	7.2
Total lighting service (lumen-hours / solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	1510

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS

Lamp name	Number of lamps	Number of settings	Setting name	Light output (lm)	Power consumption (W)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
L220	1	3	Super	210	1.1	190	68	5100	Wide	100%
			Normal	78	0.43	170	67	5100		
			Night	not tested	0.06	not tested	not tested	not tested		

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K).

^h Percent of the original light output that remains after 2,000 hours of run time.

PORTS		
5 V port		Omnivoltaic customized port for mobile charging, adaptors are included.
DURABILITY		
Overall durability and workmanship		Pass
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests
Level of water protection	Main Unit	Has protection from occasional rain; met IPX1
	PV module	Has protection from permanent outdoor exposure
SOLAR DETAILS		
PV module type		Monocrystalline silicon
PV maximum power		3 W
PV rated power		3.3 W
PV open-circuit voltage (V _{OC})		6 V
MAIN UNIT BATTERY DETAILS		
Battery replaceability		Not easily replaceable with common tools.
Battery chemistry		Lithium-ion
Specific Li-ion battery chemistry		lithium nickel manganese cobalt oxide
Battery package type		18650
Battery capacity		3.1 Ah
Rated Battery capacity		3.2 Ah
Battery nominal voltage		3.6 V
Battery status / other indicator lights		Three indicators for battery state of charge.
PRODUCT DETAILS		
Company name		Omnivoltaic Energy Solutions Co., Ltd. / Omnivoltaic (Shenzhen) Co., Ltd
Brand Name		Omnivoltaic
Product name		L220 Task Light & Phone Charger
Product model / ID number		L220
Contact information		sales@omnivoltaic.com / alpha_guo@omnivoltaic.com
Website		www.omnivoltaic.com
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.
Mass		n/a
SSS INFORMATION		
Specs sheet expiration date		November 30, 2026
Revision		2025.06