

Mobiya Original

AEP-LU01-S2000

Brand name: Schneider Electric Industries SAS

Verify online:

<https://data.verasol.org/products/sek/se-org-blue>

Results based on test procedures detailed in IEC TS 62257-9-5

Valid until: March 31, 2026



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging

1

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects

PERFORMANCE DETAILS

				Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	1 light point on turbo, totaling 270 lumens and 2.3 W power	4.1 hours	1.9 hours
no	not included	Smart phone	Smart phone (5.7 Wh battery)	0.93 full charge(s)	0.49 full charge(s)

Available daily electrical energy ^e (Wh/day)	7.6
---	-----

Performance measure	Brightness setting: turbo
Lighting full battery run time ^d for main unit (hours)	4.6
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	1110

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS


Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Power consumption (W)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
Main Lighting Unit	1	4	Turbo	270	2.3	120	90	5200	Wide	99%
			High (Not tested)	250 (Rated value)	Not tested	Not tested	Not tested	Not tested	Not tested	Not tested

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

PORTS		
1	USB 2.0 type A	 Mobile phones can be charged. Adapters are included.
DURABILITY		
Overall durability and workmanship		Pass
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests
Level of water protection	Main Unit	Has protection from permanent outdoor exposure; met IPX7
	PV module	Has protection from permanent outdoor exposure
SOLAR DETAILS		
PV module type		Polycrystalline silicon
PV maximum power		2.6 watts
PV rated power		2.5 watts
PV open-circuit voltage (V _{OC})		5.5 volts
MAIN UNIT BATTERY DETAILS		
Battery replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.
Battery chemistry		Lithium iron phosphate
Battery package type		26650
Battery capacity		3.42 Ah
Battery nominal voltage		3.2 V
Battery status / other indicator lights		Two indicators for PV charging and battery
PRODUCT DETAILS		
Company name		Schneider Electric Industries SAS
Product name		Mobiya Original
Product model / ID number		AEP-LU01-S2000
Contact information		sathish.kumar@se.com; adarsh.tv@se.com
Website		www.se.com
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.
Mass		1081 g
SSS INFORMATION		
Specs sheet expiration date		March 31, 2026
Revision		2025.12