Solar Media Home Lighting System SR77A Shenzhen Power-Solution Ind Co., Ltd.



Meets the Lighting Global Pico-PV Quality Standards



Mobile charging



Light point(s)



Plug-and-play



Run time after a typical day of solar charging

There is a "2 years warranty". The warranty is void for normal wear and tear, and is void for the defects caused by abnormal use, rough handling and misuseof product. There is a 1 year warranty for the optional home appliances.

PERFORMANCE DETAILS

				(assuming 5kWh/m²/day)			
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c		
yes	included	Main lighting unit	3 light points on (On) totaling 490 lumens and 4.5 W power	5.1 hours	3.3 hours		
yes	included	Video Display	7" integrated video display with a power consumption of 1.6 W while in use on the highest volume	16 hours	1.9 hours		
no	not included	Mobile phone	Basic phone (3.7 Wh battery)	4.8 full charge(s)	1.1 full charge(s)		

Available daily electrical energy ^c (Wh/day) 23
--

Performance measure	Brightness setting: On		
Lighting full battery run time ^d for main unit (hours)	5.3		
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	1620		

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCTg	Distribution type	Lumen maintenance ^h
LED bulb	3	1	On	170	95	74	7200	Wide	100%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

⁹ Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATU	RES						
Data transmit and charging port		The control box contains an USB port which allows data transmit and phone charging.					
PORTS							
2	USB 2.0 type A		One USB output port for phone charging and one USB output port for data transmit.				
3	Barrel jack	-	Three 6 V output ports for LED bulbs.				
Overall durability	and workmanshin		Pass				
Overall durability and workmanship Durability tests passed			Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests				
- Durability tests pa							
		Main Unit	Water ingress protection not tested, meant for indoor use only.				
Level of water protection		PV module	Has protection from permanent outdoor exposure.				
Level of water pro	ic cuon	LED bulb	Water ingress protection not tested, meant for indoor use only.				
		Remote Controller	Water ingress protection not tested, meant for indoor use only.				
SOLAR DETAILS							
PV module type			Polycrystalline silicon				
PV maximum pow	/er		10 watts				
MAIN UNIT BATT	ERY DETAILS						
Battery replaceab	ility		Easily replaceable with common tools.				
Battery chemistry			Lithium iron phosphate				
Battery capacity			5.9 Ah				
Battery nominal voltage			6.4 V				
Battery status indi	cation		One LED for remote control receiver and four LEDs for showing battery statusand working status				
MARKS AND CE	RTIFICATIONS						
Factory certification	n		ISO 9001; ISO 45001; ISO14001				
PRODUCT DETA	ILS						
Manufacturer nam	ne		Shenzhen Power-Solution Ind Co., Ltd.				
Product name			Solar Media Home Lighting System				
Product model / ID	number		SR77A				
Contact information			susan@power-solution.net.cn				
Website			https://www.power-solution.net.cn/				
Co-brand of			Solar Media Home Lighting System, ShenZhen Solar Run Energy Co., Ltd.				
Dimensions (entire product in package)			25 x 35 x 9 cm				
Mass			2480 g				
SSS INFORMATIO	N						
Specs sheet expiration date			October 31, 2022				
Quality standards framework version			2021				
Revision			2021.09				