

Meets the Requirements in IEC TS 62257-9-8:2020 for Size B kits



Mobile charging



Light point(s)





Run time after a typical day of solar

1.6 full charge(s)

9.4 full charge(s)

WARRANTY INFORMATION

PERFORMANCE DETAILS

no

A 3-year warranty covering manufacturing defects in the system for the PV module, control box, cables, lights, and battery. A 1-year warranty for the non-lighting appliances and USB adapters.

					ging kWh/m²/day)
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	3 light points on "On" totaling 690 lumens and 4.8 W power	6.8 hours	5.9 hours
yes	included	Radio	portable (Li-ion battery: 1.5 Ah, 3.7 V), with a power consumption of 0.45 W while in use	86 hours	4.9 hours

Basic phone (3.7 Wh battery)

38

Mobile phone

Performance measure	Brightness setting: 3 lights on "On"
Lighting full battery run time ^d for main unit (hours)	6.8
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	4690

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

not included

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS										
Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Power consumption (W)	Lumen efficacy ^e (Im/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
1.7 W lamp	3	1	On	230	1.6	140	81	6500	Wide	100%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^fColor Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

PORTS			
2	USB 2.0 type A	Mobile phones and radios can be charged. Adapters are included.	
3	Barrel jack	6.4 V ports available to power light points.	

DURABILITY					
Overall durability and workmanship		Pass			
Durability tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests			
	Main Unit	Water ingress protection not tested, meant for indoor use only.			
	PV module	Has protection from permanent outdoor exposure			
Level of water protection	Radio	Has protection from occasional rain; met with appropriate warning label			
	1.7 W lamp	Water ingress protection not tested, meant for indoor use only.			
SOLAR DETAILS					
PV module type		Polycrystalline silicon			
PV maximum power		16 watts			
PV rated power		15 watts			
PV nominal voltage		9 volts			
MAIN UNIT BATTERY DETAILS					
Battery replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.			
Battery chemistry		Lithium iron phosphate			
Battery package type		32700			
Battery capacity		6 Ah			
Battery nominal voltage		6.4 V			
Battery status/ other indicator lights		4 indicators that show the battery level and charging condition.			
PRODUCT DETAILS					
Company name		Shenzhen Solar Run Energy Co., Ltd.			
Brand Name		Solar Run			
Product name		Eco Box			
Product model / ID number		SR24C32YG			
Contact information		info@solarunoffgrid.com			
Website		www.solarunoffgrid.com			
Co-brand of		Energy Station Next, OffGridSun			
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.			
Mass		n/a			
SSS INFORMATION					
Specs sheet expiration date		September 30, 2025			
Revision		2024.09			